

REGAL AQUA MATT EMULSION

GENERAL DESCRIPTION Primax Regal Velvet Touch Aqua Matt Emulsion is exclusive high quality water based matt emulsion. Odorless and low VOC with a soft matt finish. It is suitable for all interior masonry surfaces including brickwork, plaster cement rendering, and wall boards. Household stains for example coffee, tea, ketchup, juice, oil, etc.

PACK SIZE 1liter, 4 liters, and 16 liters.

COLOUR RANGE See Regal Velvet Touch Aqua Matt Emulsion shade card.

COMPOSITION (NOMINAL) Pigment: Lightfast Pigments
Binder: Acrylic Copolymer Emulsion.
Solvent: Water

DRYING TIMES Depends on temperature, humidity, air movements and film thickness.
Touch dry 2 - 3 Hours
Recoat 4 - 6 Hours

THEORETICAL COVERAGE A guide to the theoretical coverage which can be achieved under normal conditions are is10-13 m² /liter /coat.

APPLICATION: Brush, Roller, Spray

THINNING
Brush or Roller 20 - 30%
Spray 30-40%

CLEANING UP Clean all equipment with water immediately after use.

SURFACE PREPARATION

New, bare, old, or previously painted surfaces must be clean, dry, and free from dust or wax, Clean the surface by rubbing it down with abrasive paper. Brush down the previously painted surface completely and make the surface smooth. For large holes and cracks, use Plaster of Paris or White Cement. Allow to dry. Apply Primax Regal Interior Primer in order to seal the surface from water and salts. Allow the surface to dry completely then apply Primax Regal Interior Filler and allow to dry. Rub down the surface with abrasive paper and dust off.



PRIMAXTM
PAINTS

After preparation apply 2-3 coats of Primax Regal Velvet Touch Aqua Matt Emulsion.

FLASHPOINT

N/A

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



PRIMAXTM
PAINTS