

REGAL[®] EXTERIOR WALL PUTTY

GENERAL DESCRIPTION Primax Regal Exterior Wall Putty is 100% acrylic based ready to use exterior putty that has good whiteness, coverage and application properties. It provides even and smooth base for Topcoats. It is APEO and formaldehyde Free.

PACK SIZE 20 Kg Only

COLOUR RANGE White Only

COMPOSITION (NOMINAL) Pigment: Inert Fillers
Binder: Acrylic Copolymer Emulsion.
Solvent: Water

DRYING TIMES Depends on temperature, humidity, air movements and film thickness.
Touch dry 2 - 3 Hours
Recoat 3 - 4 Hours

THEORETICAL COVERAGE A guide to the theoretical coverage which can be achieved under normal conditions is 4-6m²/liter /coat.

APPLICATION: Putty applicator

THINNING Ready to Use

CLEANING UP Clean all equipment with water immediately after use.

SURFACE PREPARATION

New or bare surfaces must be clean, dry, and free from efflorescent salts.

Remove all defective or poorly adhering material by rubbing down using suitable abrasive paper or stiff brushes and dusting off. Treat any area affected by mold, or lichens. Algae or moss with bleach. After priming new surfaces with Primax Regal Primer, fill the surface with Primax Regal Exterior Wall Putty. Allow the filler to dry for 2-3 hrs. and apply a second coat of Primax Regal Exterior Wall Putty. Primax Regal Exterior Wall Putty water-based can also be applied directly on new unpainted surfaces. Primax Regal Exterior Wall Putty water-based is not recommended for exterior use.



PRIMAXTM
PAINTS

After surface preparation apply 2-3 coats of Primax Regal Decorative paint.

FLASH POINT

N/A

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



PRIMAXTM
PAINTS