

REGAL[®] MATT FINISH

Primax Regal Matt Finish Enamel provides a hardwearing and non-dazzling effect with excellent resistance to moisture and steam. It has good stain resistant properties and excellent Washability.

USES

It is suitable and ideal for interior wood, metal, and masonry works. Primax Matt Finish Enamel is especially recommended for bathrooms, kitchens, corridors, staircases, and walls.

PACK SIZE: 0.91L 3.64L

COLOR RANGE: See Primax Regal Matt Finish Enamel shade card

FILM PROPERTIES: Chemical Resistance: Resistant to mild chemical fume attack.
Water Resistance: Resistance to the levels of atmospheric humidity present in a normal environment.

COMPOSITION (NOMINAL) :

Pigment: Lightfast Pigments

Binder: Modified Alkyd Resin

Solvent: Mineral Turpentine

DRYING TIME:

Depends on temperature, humidity, air movements, and film thickness.

Touch Dry: 2-4 Hours

Dry to Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 14-16m²/liter/coat.

APPLICATION: Brush Roller Spray

THINNING Brush/Roller 10-15%



PRIMAXTM
PAINTS

Spray 20-25%

FLASHPOINT: 34°C

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPARATION:

New or bare surfaces, must be clear, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. all surface should be thoroughly rubbed down using a suitable abrasive paper and then dusted off. Fill all surface defects, cracks with a suitable filler. When dry rub down smooth and dust off.

APPLICATION RECOMMENDATIONS

Use Wood Primax Synthetic Undercoat prior than One Coat Metal Primax Red Oxide Primer after it do one Coat Masonry Primax Wall Primer Sealer or Primax Undercoat. One or two coats according to surface requirement. Finishing 2 or 3 coats of Primax Matt Enamel.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.

