

REGAL[®] MULTI TILE

Primax Multi Tile is a good quality texture required to make multi tile finishes for decorative purposes. It is a heavy body, moldable texture, having properties like mildew resistance, breathability and water proofing etc. It is suitable for making different textures on all plasters, concrete and wood etc.

PACK SIZE: 5kg 20kg

COLOR RANGE: White only

COMPOSITION (NOMINAL):

Pigment: Lightfast Pigments & Inert Extenders

Binder: Acrylic Copolymer

Solvent: Water

FILM CHARACTERISTICS

This Multi Tile resists heavy abrasion, cracking and chipping, Mildew Growth, Water resistant.

FLASH POINT: N/A

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 20-30 Minutes

Overcoming Coating: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 1-2m²/liter/coat.

APPLICATION: Special multi-til gun

THINNING:

Not Required

CLEANING UP:

Clean all equipment with water immediately after use.

SURFACE PREPARATION:

The surface should be clean, dry, and free from efflorescent salts and loosely adhering matter, remove dirt, grease, and waxy material. Apply a coat of Primax Wall Primer Sealer, Spray the multi tile with a gun adjusting the nozzle and the distance between the gun and the surface.



Leave for at least 24 hours, scuff and coat with Weather Care, Enamel, Metallic Paint, Varnish etc. We can make it two, three or even four toned multi-tile. The beauty and the type very much depends upon the painter.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO₂ fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation



PRIMAXTM
PAINTS