

REGAL[®] PAINT REMOVER

PRODUCT DESCRIPTION:

Primax Paint Remover is a fast reactive, slow evaporating compound which on application swells the old paint and enables its easy removal. It is used to remove paint from all types of surfaces.

PACK SIZE: 0.91 L

COLOR RANGE: Clear

COMPOSITION (NOMINAL):

Pigment: N/A

Binder: N/A

Solvent: Blend of Volatile Solvents

FILM THICKNESS/COAT: N/A

DRYING TIME

Touch Dry: N/A

Recoat: N/A

THEORETICAL COVERAGE: N/A

APPLICATION: Stiff brush, Brush or spatula

THINNING: NA

CLEANING UP:

Clean all equipment with water.

SURFACE PREPARATION: N/A

APPLICATION METHOD

Remove direct, grease from the surface, Apply Primax Paint Remover with brush or spatula and allow sufficient time for the film to become soft before removing it with a scrapper. Softening of the paint depends upon the types of thickness of the paint. Do not allow the paint remover to dry on the surface. For every hard paints like baking/Boiler Paints make deep scratches with the help of a sharp knife, it will help penetrate the paint remover. Residues remaining after scrapping off the paint should be carefully removed by scuffing and washing with water. The surface then should thoroughly be dried and finally wiped with rag soaked in petrol before repainting in undertaken. In case of wood it should be left on



PRIMAXTM
PAINTS

minimum possible time or it will penetrate the wood and will effect subsequent paint coatings, thoroughly wash the surfaces paying particular attention to cracks and corners.

SPECIAL INSTRUCTIONS:

Open the tin carefully as the solvent is fast evaporating and material may come out with pressure. It is very irritating and may cause damage to your eyes. Place the tin in cool environment and protect it from direct heat.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. protect from extremes of temperature, store in a cool and dry place. It may explode with heat. Keep away from food, drink and animal feed. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is in conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire, use foam, dry powder, CO₂ fire extinguisher. Never use water. Take precautionary measures against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.



PRIMAXTM
PAINTS