

# REGAL<sup>®</sup> PLASTIC EMULSION

**GENERAL DESCRIPTION** Primax Regal Plastic Emulsion is a high quality 100% Acrylic based emulsion paint for new and previously painted interior & exterior masonry surfaces such as brick work, plaster and cement rendering.

**PACK SIZE** 1liter, 4 liters and 16 liters.

**COLOUR RANGE** See Regal Plastic Emulsion shade card.

**COMPOSITION (NOMINAL)** Pigment: Lightfast Pigments  
Binder: Acrylic Copolymer Emulsion.  
Solvent: Water

**DRYING TIMES** Depends on temperature, humidity, air movements and film thickness.  
Touch dry 2 - 3 Hours  
Recoat 4 - 6 Hours

**THEORETICAL COVERAGE** A guide to the theoretical coverage which can be achieved under normal conditions is 13-16m<sup>2</sup> /liter /coat.

**APPLICATION:** Brush, Roller, Spray

**THINNING**  
Brush or Roller 50 - 75%  
Spray 25%

**CLEANING UP** Clean all equipment with water immediately after use.

## **SURFACE PREPARATION**

Allow all new surfaces to dry out completely. Remove all loose, defective paint or powder residues by thorough brushing or scraping using a stiff brush. Treat any area affected by mold, lichens, algae or moss with bleach. Make good minor defects. For large holes and cracks use sand and cement mixture. Allow to dry, surface that remain powdery should be sealed with a coat of Primax Regal Acrylic Primer.

After preparation apply 3-4 coat of Primax Regal Plastic Emulsion.

**FLASHPOINT** N/A



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO<sub>2</sub> fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.

