

# REGAL<sup>®</sup> SYNTHETIC UNDERCOAT

Primax Synthetic Undercoat is quick drying undercoat with excellent filling and good adhesion properties. Overnight air drying makes the primer easily sand able. It can be over coated with synthetic enamel, hammer tone and metallic finishes including automotive lacquers.

**PACK SIZE:** , 0.91 Litre 3.64 Litre.

**COLOR RANGE:** Light Grey, White, pink and green

## **COMPOSITION (NOMINAL):**

Pigment: Inert Filler and Lightfast Pigments

Binder: Alkyd Resin

Solvent: Mineral turpentine

## **DRYING TIME:**

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 1-2 Hours

Recoat: 4-6 Hours

## **THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 9-11m<sup>2</sup>/litre/coat.

**APPLICATION:** Brush Roller Spray

**THINNING:** Mineral Turpentine / Primax Mixing Oil

Brush or Roller: 10-25%

Conventional spray: 30-40%

**FLASH POINT** 34 degree C

## **RECOMMENDATIONS:**

Conventional spray is satisfactory through most equipment.



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **CLEANING UP:**

Clean all equipment with mineral turpentine immediately after use.

## **SURFACE PREPARATIONS:**

Prior to starting painting surface should be clean, free from dirt, grease and other foreign materials for achieving good results. Apply two coats of Primax Synthetic Undercoat. Give 8-16 hours between the coats for drying. As the undercoat is highly pigmented it should not be left unpainted for long time. After overnight hard drying the surface is sanded / wet flatted with 320 or 400 grade sanding paper. Wipe the surface dry and then with petrol soaked cloth to get rid of oily finger marks before over coating.

## **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO<sub>2</sub> fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation



**PRIMAX**<sup>TM</sup>  
**PAINTS**