

# REGAL<sup>®</sup> SYNTHETIC CLEAR VARNISH

Primax synthetic clear varnish is an air-drying very high gloss varnish for wood and metal surfaces. For improvement of gloss it can be mixed with synthetic enamels. It gives tough, flexible and hard wearing finish. It is suitable for all types of wood and steel surfaces. Wood and cane-furniture, doors, windows and tongas, etc.

**PACK SIZE:** 0.25L 0.75L 3L 12L

**COLOR RANGE:** Clear

**COMPOSITION (NOMINAL):**

Pigment: N/A

Binder: Alkyd Resin

Solvent: White spirit / Primax Mixing Oil

**THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 11-13m<sup>2</sup> /litre/coat.

**FLASH POINT:** 33°C

**DRYING TIME:**

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 6-8 Hours

**APPLICATION:** Brush & Spray

**THINNING**

Brush or Roller: 10-20%

Conventional spray: 30-40%

**SURFACE INFORMATION:**

**NEW SURFACES**

Clean wood or metal surface by scuffing with abrasion paper, dust off, wipe and clean with solvent soaked cloth and apply Primax Synthetic Clear Varnish. Prior to apply varnish grain filling should be done.

**OLD SURFACES**

Wash dirt, grease or wax etc. from the surface of previously varnished objects with detergent water, scuff the surface with suitable sandpaper. Remove all loosely adhering varnish by scrapping, if the previous varnish is flaking or in poor condition get rid of all debris, scuff to smoothness of the surface, dust off and apply Primax Synthetic Clear Varnish (two coats) by brush or spray.



**PRIMAX**<sup>TM</sup>  
**PAINTS**

**SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:**

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation



**PRIMAX**<sup>TM</sup>  
**PAINTS**