

REGAL[®] TEXTURE FINISH

Primax Regal Texture Finish is a good quality texture required to make different textures for decorative purpose. It is a heavy-body, mold able texture, having properties like mildew resistance, breath ability and water proofing etc. It is suitable for making different textures on walls, plasters, concrete and wood etc. It can be used both exterior and interior.

PACK SIZE: 5kg, 20kg

COLOR RANGE: White only

COMPOSITION (NOMINAL):

Pigment: Lightfast Pigments & Inert Extenders

Binder: Acrylic Copolymer

Solvent: Water

FLASH POINT: N/A

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 20-30 Minutes

Overcoming Coating: 3-4 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 3-4m²/litre/coat.

APPLICATION: Spatula, Italian Knife, Scraper, Texture Roller, Design Roller

THINNING:

Not Required

CLEANING UP:

Clean all equipment with water immediately after use.

SURFACE PREPARATION:

Sand the surface with sandpaper and apply a coat of Primax Wall Primer Sealer. Its application only and only depends upon the painter and the texture required. In some cases Primax Wall Putty is must, in others, it is not required.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc.



PRIMAXTM
PAINTS

Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.



PRIMAXTM
PAINTS