

REGAL[®] TONERS

Primax Regal Toner is a topcoat delivers outstanding gloss and appearance. Available for use in all markets, this easy-to-use toner is ideal for large repairs, or where a high gloss finish is desired.

PACK SIZE: 0.25, 0.91L & 3.64L

COLOR RANGE: Green, Silver, Blue & Crimson

COMPOSITION (NOMINAL):

Pigment: Lightfast Pigments

Binder: Alkyd Resin

Solvent: Mineral Turpentine

DRYING TIME:

Depends on temperature, humidity, air movements, and film thickness

Touch Dry: 2-4 Hours

Dry to Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 12-14m²/liter/coat.

APPLICATION: Brush Roller Spray

THINNING	Brush/Roller	10-15%
	Spray	20-25%

FLASH POINT: 34°C

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPARATION:



PRIMAXTM
PAINTS

New or bare surfaces must be clean, dry free from dirt, grease, wax etc. Prime with PRIMAX Primer.

Surface must be clean, dry, free from all defective or poorly adhering material dirt, grease, wax etc. All surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off. Fill all surface defects, cracks with a suitable filler. When dry rub down smooth and dust off.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO₂ fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation



PRIMAXTM
PAINTS