

REGAL[®] WALL PRIMER SEALER

Primax Regal Wall Primer Sealer as its name indicates acts as a sealer for masonry plaster and concrete surfaces. It prevents damage from alkali and salts. It seals the porous surfaces and thus reduces the consumption of top-coats. It also improves adhesion. It is suitable for concrete and plaster surfaces, brick work and ceiling etc. It is also used to seal the poor distempers and lime wash coated surfaces.

PACK SIZE: 1L 4L 16L

COLOR RANGE: White only

COMPOSITION (NOMINAL):

Pigment: Stable Pigments, Inert Extender

Binder: Alkali Resistant Polymer

Solvent: White spirit / Primax Mixing Oil

FLASH POINT: 33°C

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 2 - 4 Hours

Recoat: 4 - 6 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 8 – 11 m²/liter /coat.

APPLICATION: Brush Roller Spray

THINNING:

Brush or Roller: 10 - 25%

Conventional spray: 30 - 40%

CLEANING UP:

Clean all equipment with water immediately after use.

SURFACE PREPARATION:

NEW SURFACE

Scuff the surface with rubbing stone to remove any loose and friable material. Check that the surface is dry. Then apply a coat of Primax Regal Wall Primer Sealer.



PRIMAXTM
PAINTS

OLD SURFACE

Scrap down the old paint, especially the white wash to bare the surface. Then wash with spray water to remove all the loose material. Then dry and apply a coat of Primax Wall Primer Sealer.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO₂ fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



PRIMAXTM
PAINTS