

# REGAL<sup>®</sup> WATER BASED ACRYLIC PRIMER

Primax Regal Acrylic Primer is a water-based primer for all types of exterior & interior masonry surfaces, both new and previously decorated such as brickwork, plaster, and cement. It reduces damage from alkalis, and salts, and seals the surfaces.

**PACK SIZE:** 1L, 4L, 16L

**COLOR RANGE:** White only

**COMPOSITION (NOMINAL):**

Pigment: Lightfast Pigments

Binder: Acrylic Copolymer

Solvent: Water

**FLASH POINT:** N/A

**DRYING TIME:**

Depends on temperature, humidity, air movements, and film thickness

Touch dry: 2-3 Hours

Recoat: 6-8 Hours

**THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 13-20m<sup>2</sup>/liter/coat.

**APPLICATION:**

Brush Roller Spray

**THINNING:**

Brush or Roller: 10-25%

Conventional spray: 30-40%

**CLEANING UP:**

Clean all equipment with water immediately after use.

**SURFACE PREPARATION:**

New, bare, old, or previously painted surfaces must be clean dry, and free from wax and dust. Clean the surface by rubbing it down with abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. Dust it off with the help of a cloth. Stir the paint thoroughly before use.



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION:**

Highly inflammable. Keep the container tightly closed, upright, and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter, etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink, and animal feeding stuff. Keep the container tightly closed. Wear suitable gloves, masks, and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to the eyes, skin, and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse your mouth with plenty of water (only if the person is in conscious) and show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO<sub>2</sub> fire extinguisher. Never use water. Take precautionary measures against static charges. Use only in well ventilated places. Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.



**PRIMAX**<sup>TM</sup>  
**PAINTS**