

# REGAL<sup>®</sup> SYNTHETIC ENAMEL

Primax Regal Synthetic Enamel is high quality solvent-based super gloss finish, suitable for use on all types of interior and exterior wood and metal surfaces. Primax Regal Synthetic Enamel gives a smooth mirror-like finish and has excellent durability.

**PACK SIZE:** 0.25L 0.91L 3.64L 14.56L

**COLOR RANGE:** See Primax Regal Synthetic Enamel shade card

**FILM PROPERTIES:** Chemical Resistance: Resistant to mild chemical fume attacks.  
Water Resistance: Resistance to the levels of atmospheric humidity present in a normal environment.

## COMPOSITION (NOMINAL):

Pigment: Lightfast Pigments

Binder: Alkyd Resin

Solvent: Mineral

Turpentine

**DRYING TIME:** Depends on temperature, humidity, air movements, and film thickness

Touch Dry: 2-4 Hours

Dry to Recoat: 6-8

Hours

## THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 12-14m<sup>2</sup>/liter/coat.

**APPLICATION:** Brush Roller Spray



**PRIMAX**<sup>TM</sup>  
**PAINTS**

<b>THINNING</b>	Brush Roller	10-15%
	Spray	20-25%

**FLASH POINT:** 34°C

### **CLEANING UP:**

Clean all equipment with mineral turpentine immediately after use.

### **SURFACE PREPARATION:**

New or bare surfaces must be clean, dry, and free from dirt, grease, wax, etc. After rubbing down with abrasive paper prime with an appropriate Primax Regal Synthetic Undercoat.

Surfaces must be clean, dry, and free from all defective or poorly adhering material, dirt, grease, wax, etc. All surfaces should be thoroughly rubbed down using suitable abrasive paper and then dusted off. Fill all surface defects and cracks with a suitable filler. When dry rub down, smooth, and dust off. After surface preparation apply 2-3 coats of Primax Regal Synthetic Enamel.

### **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO<sub>2</sub> fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.



**PRIMAX**<sup>TM</sup>  
**PAINTS**