

REGAL[®] SUPER EMULSION

GENERAL DESCRIPTION Primax regal super emulsion is a good quality interior emulsion with a high spreading rate tough & durable film. It contains anti-fungal & anti-bacterial additives. It exhibits good brush & recoat ability. It gives good flow and a smooth flat finish for newly & painted interior surfaces.

PACK SIZE 0.91 liters, 3.64 liters, and 14.56 liters.

COLOUR RANGE See the Super emulsion shade card.

COMPOSITION (NOMINAL) Pigment: Lightfast Pigments
Binder: PVA Copolymer Emulsion.
Solvent: Water

DRYING TIMES Depends on temperature, humidity, air movements, and film thickness.

Touch dry 2 - 3 Hours
Recoat 4 - 6 Hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

COVERAGE conditions is 11-16m² /liter /coat.

APPLICATION: Brush, Roller, Spray

THINNING
Brush or Roller 15- 25%
Spray 50-75%

CLEANING UP Clean all equipment with water immediately after use.

SURFACE PREPARATION

Allow all new surfaces to dry out completely. Remove all loose, defective paint or powder residues by brushing or scraping using a stiff brush. Treat any area affected by mold, lichens, algae, or moss with bleach. Make good minor defects, for large holes and cracks use a sand and cement mixture. Allow to dry, surface that remains powdery should be sealed with a coat of Primax Regal primer. After preparation apply 3-4 coats of Primax Regal Super Emulsion.

FLASHPOINT N/A



PRIMAXTM
PAINTS

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO₂ fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



PRIMAXTM
PAINTS