

# POWER<sup>®</sup> SILK EMULSION

**GENERAL DESCRIPTION** Primax Power Silk Emulsion is top quality interior Emulsion paint with a smooth and slightly glossy finish. It is suitable for all interior surfaces including cement concrete plaster, chipboard, and hardboard.

**PACK SIZE** 0.91 liters, 3.64 liters, and 14.56 liters.

**COLOUR RANGE** See Primax Power Silk Emulsion shade card.

**COMPOSITION (NOMINAL)** Pigment: Lightfast Pigments  
Binder: PVA Copolymer Emulsion.  
Solvent: Water

**DRYING TIMES** Depends on temperature, humidity, air movements and film thickness.  
Touch dry 2 - 3 Hours  
Recoat 4 - 6 Hours

**THEORETICAL COVERAGE** A guide to the theoretical coverage which can be achieved under normal conditions is 13-15m<sup>2</sup> /liter /coat.

**APPLICATION:** Brush, Roller, Spray

**THINNING**  
Brush or Roller 10 - 25%  
Spray 50-75%

**CLEANING UP** Clean all equipment with water immediately after use.

## SURFACE PREPARATION

Allow all new surfaces to dry out completely. Remove all loose, defective paint or powder residues by brushing or scraping using a stiff brush. Treat any area affected by mold, lichens, algae, or moss with bleach. Make good minor defects, for large holes and cracks use a sand and cement mixture. Allow to dry, the surface that remains powdery should be sealed with a coat of Primax Regal primer. After preparation apply 3-4 coats of Primax Power Silk Emulsion.

**FLASH POINT** N/A



## **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

Keep the container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. A cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contact with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from the skin, use soap and water or a recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from the source of ignition. Close the container tightly after each use. Keep out of reach of children. In case of an accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance, or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



**PRIMAX**<sup>TM</sup>  
**PAINTS**