

REGAL[®] RED OXIDE PRIMER

PRIMAX REGAL RED OXIDE PRIMER is a high quality solvent based anti-corrosion protective primer for interior and exterior ferrous and non-ferrous metalwork including new and pre-treated zinc and galvanized iron. It may also be applied over pre-treated aluminum.

PACK SIZE: 0.91 Ltr., 3.64 Ltr. and 14.56 Ltr.

COLOR RANGE: Iron Oxide Red only

COMPOSITION (NOMINAL):

Pigment: Stable Pigments, Inert Extender

Binder: Modified Alkyd Resin

Solvent: mineral turpentine oil

FLASH POINT: 33°C

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 2 - 4 Hours

Recoat: 4 - 6 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 14 – 16 m²/liter /coat.

APPLICATION: Brush, Roller, Spray

THINNING:

Brush or Roller: 10 - 20%

Conventional spray: 20 – 25%

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPARATION:

Surfaces must be clean, dry and free from defective or poorly adhering material dirt, grease, wax etc. Previously painted surfaces should be thoroughly rubbed down using suitable abrasive paper and then dusted off.

New galvanized and aluminum surfaces should be cleaned and degreased. Then pre-



PRIMAXTM
PAINTS

treated with an appropriate pre- treatment primer to ensure good adhesion. After surface preparation apply 2-3 coat of Primax Regal Synthetic Enamel top coat.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contact with eyes and skin.

Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.



PRIMAXTM
PAINTS