

# REGAL<sup>®</sup> INTERIOR AQUA PRIMER

**GENERAL DESCRIPTION** Primax Regal interior Aqua Primer is a water based wall sealer formulated to provide maximum protection against alkali and moisture, enhancing the performance of top coat. It is a breathable Primer that stops water from entering the surface, but allows water vapour out. It has good intercoat adhesion. This Interior Primer is recommended for use on interior plastered walls, ceilings, concrete, brickwork and wall boards, etc.

**PACK SIZE** 3.64 liters and 14.56 liters.

**COLOUR RANGE** White Only

**COMPOSITION (NOMINAL)** Pigment: Lightfast Pigment  
Binder: PVA Copolymer Emulsion.  
Solvent: Water

**DRYING TIMES** Depends on temperature, humidity, air movements and film thickness.

Touch dry 2 - 3 Hours

Recoat 3 - 4 Hours

**THEORETICAL** A guide to the theoretical coverage which can be achieved under normal

**COVERAGE** conditions is 13-15m<sup>2</sup> /liter /coat.

**APPLICATION:** Brush, Roller, Spray

## THINNING

Brush or Roller 20 - 40%

Spray 40-60%

**CLEANING UP** Clean all equipment with water immediately after use.

## SURFACE PREPARATION

New, bare, old previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks use Plaster of Paris or White Cement, Allow to dry. Apply Primax Regal Interior Aqua Primer in order to seal the surface from water and salts. Allow surface to dry completely. Stir the paint thoroughly before use.

**FLASH POINT** N/A



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



**PRIMAX**<sup>TM</sup>  
**PAINTS**