

Royal Exclusiv pumps & skimmers

Vorgebirgsstr. 28 // 50389 Wesseling // Germany

Fon +49(0)2236/88055-0 // Fax +49(0)2236/88055-20

info@royal-exclusiv.de // www.royal-exclusiv.de



Since 1986




Data sheet and list of spare parts for Red Dragon® 3 pump HIGH PRESSURE VERSION

For all Red Dragon® 3 Speedy 150 Watt / 17,0m³ pumps (High Pressure)

v1.0

ENG







Data sheet and power curve for pressure pump with adjustable speed motor

Red Dragon[®] 3 Speedy pump 150 Watt / 17,0m³ Product no.: **605/HP** **1.120,00 €**

Technical data Red Dragon[®] 3 Speedy pump 150 Watt / 17,0m³:

Performance: 17.100 liter / h
Cable length: 0,8 meter (plug controller)
3,8 meter (controller to pump)
pump and controller with a removeable Hirschmann-plug-connection

Pressure side: Ø 40 mm Intake side: Ø 50 mm
Wattage: adjustable max. 150 Watt (min. 20W, in 2 W steps)
Pressure height: max. 6,35 meter
Material/color: PVC black/red/grey with screw connection
Operating voltage: 230 Volt 50 Hz (also in 110V/60Hz available)
Noise level: 39 - 47 db at full speed (measured in 1 m distance - operation external)
Protection class: IP 68 (submersible pump) IP 66 (controller)
Weight: 4,7 kg
Height of intake side: center 70 mm
Dimension pump: ~ 130 mm wide / 290 mm length / 210 mm height
Dimension controller: ~ 190 mm wide / 168 mm length (250 mm with connection cable) / ~ 84 mm height



////////////////////////////////////

- Saltwater resistant M6 grade 2 titanium screws
- Saltwater resistant parabolic rubber feet for acoustic decoupling
- Extreme low noise brushless dc-delivery pump with grouted power electronics
- High efficient technology Made in Germany
- Inlet and Outlet complete with DIN connection, compact dimensions
- High performance ceramics bearings and hollow shaft for bypass purging in the rotor housing
- "The only" saltwater resistant pump with titanium rotor, titanium stator and shrivelled bearings
- Easy usage and maintenance. Low risk of calcification due to polished titanium parts and compulsory purging
- Heavy and massive craftsmanship against vibrations and oscillation
- CE conformity, developed and built according to VDE guidelines

////////////////////////////////////

The direct control/connection of Aquarium computer possible!

Prepared for connection to an aquarium computer (E.g. GHL) via a 0-10V interface. No additional controller needed. tested so far folowing these two computers: GHL ProfiLux 3.1 and from Neptune Systems the Apex Aqua Controller.

Functioning of the electronics:

Once a voltage > 0,5V to the 10V interface is, the interface adapter takes over controlling and the system and lock(disable) the buttons on the controller. Voltage will be < 0,5V normal controller operation and the buttons are again released. So can the interface adapter stay connected without performing a function.

If the Aquarium(tank)-computer voltage under 0,5V the 0-10V interface is shut down and the pump can be operated manually. From 0,5V, the interface will take over control of the scheme. In the area of 0,5V-0,8V the pump is switched off. From ~ 0,8V starts the pump at the lowest level (20W) and run. At an increase of steps in 2W up to 9V=150W. So 1V = 20W 9V = 150W. The applied voltage and the resulting performance will be shown in the display.


At a higher input voltage remains the Speedycontroller to the maximum setting are available and no longer increases. The interface adapter behaves as if the corresponding would push the button.

For more information, please visit www.royal-exclusiv.de. Simply enter the part number or name into the search box or email: info@royal-exclusiv.de.

All information subject to change. We try our best, but printing errors reserved.

Red Dragon® 3 Speedy Pump 150 Watt / 17,0m³ // Power effective 150 ~ 155W // 47 dB 1 m distance external use

Power curve with **150W**



pressure height
in meter

pressure height inch
pressure height meter
liter / hour
gallons / hour

0"	19.69"	39.37"	59.06"	78.74"	98.43"	118.1"	137.8"	157.5"	248.0"
0m	0,5m	1,0m	1,5m	2m	2,5m	3,0m	3,5m	4,0m	6,3m(Max)
17100	15400	13700	11800	10100	8600	7500	6300	4300	0
4517	4068	3619	3117	2668	2272	1981	1664	1136	0




For more information, please visit www.royal-exclusiv.de. Simply enter the part number or name into the search box or email: info@royal-exclusiv.de.

All information subject to change. We try our best, but printing errors reserved.



Red Dragon® 3 Speedy Pump 150 Watt / 17,0m³ // Power effective 102 ~ 107W // 44 dB 1 m distance external use

Power curve with **100W**




pressure height
in meter

pressure height inch
pressure height meter
liter / hour
gallons / hour

0"	19.69"	39.37"	59.06"	78.74"	98.43"	118.1"	137.8"	187.0"		
0m	0,5m	1,0m	1,5m	2m	2,5m	3,0m	3,5m	4,75m	(Max)	
14800	12900	10900	8900	7000	5400	3700	1900	0	0	
3910	3408	2879	2351	1849	1427	977	502	0	0	

Red Dragon® 3 Speedy Pump 150 Watt / 17,0m³ // Power effective 51 ~ 56W // 41 dB 1 m distance external use

Power curve with **50W**



pressure height
in meter

pressure height inch
pressure height meter
liter / hour
gallons / hour

0"	19.69"	39.37"	59.06"	78.74"	98.43"	0"	0"	0"	0"	
0m	0,5m	1,0m	1,5m	2m	2,5m	0m	0m	0m	0m	(Max)
11300	8600	6200	4000	1800	0	0	0	0	0	
2985	2272	1638	1057	476	0	0	0	0	0	

For more information, please visit www.royal-exclusiv.de. Simply enter the part number or name into the search box or email: info@royal-exclusiv.de.

All information subject to change. We try our best, but printing errors reserved.

Red Dragon® 3 Speedy pump 150 Watt / 17,0m³ Product no.: 605/HP

list of spare parts	Product.no. (110V)	(230V)	Price
part motor-block 150/230W	606/30	606/30	455,00 €
controller for 150W (complete with power-plug-cable)	605/40/1	605/40/2	425,00 €
rotor complete 150/230W PRESSURE	606/20/HP	606/20/HP	198,00 €
pump head with AKB (anti-lime-bypass) GREY / Screw-con.	605/10	605/10	295,00 €
AKB bypass hose (anti-Lime-bypass) red hose piece	606/35	606/35	5,85 €
titan screw 6x32mm	614/12	614/12	4,61 €
titan screw 6x80mm	606/50	606/50	12,95 €
screw connection complete Ø 40mm	175-40	175-40	6,83 €
screw connection complete Ø 50mm	175-50	175-50	7,25 €
o-ring for pump head Ø 95mm x 3mm	606/15	606/15	4,95 €
o-ring intake side Ø 40mm	174-40	174-40	1,78 €
o-ring pressure side Ø 50mm	174-50	174-50	2,00 €
rubber feet set = 4 pieces	180	180	4,20 €
rotor complete 150/230W FLOW	606/20	606/20	186,00 €

accessories	Product.no. (110V)	(230V)	Price
silicon anti-vibration pump head GREY Outtake 50mm	119-50	119-50	49,90 €
silicon anti-vibration pump head GREY Intake 40mm	119-40	119-40	39,90 €
silicon grease tube 6g	030/6	030/6	2,63 €
silicon grease tube 25g	030/25	030/25	7,88 €

accessories



silicon anti-vibration 50mm
for pump head GREY
119-50

accessories



silicon anti-vibration 40mm
for pump head GREY
119-40

accessories



silicon grease tube 6g
030-6

For more information, please visit www.royal-exclusiv.de. Simply enter the part number or name into the search box or email: info@royal-exclusiv.de.

All information subject to change. We try our best, but printing errors reserved.

Red Dragon® 3 Speedy pump 150 Watt / 17,0m³ Product no.: 605/HP

spare part



part motor-block 150/230W
606/30

spare part



controller 150W (complete)
605/40-x

spare part



rotor complete 150/230W
PRESSURE version
606/20/HP

spare part



pump head GREY 40/50
with AKB (anti-lime-bypass)
605/10

spare part



rubber feet set = 4 pieces
180

spare part



AKB (anti-lime-bypass)
piece red hose
606/35

spare part



titan screw 6x32mm
614/12

spare part



titan screw 6x80mm
606/50

spare part




screw connection
complete 40mm with o-ring
175-40

spare part



screw connection
complete 50mm with o-ring
175-50

spare part



o-ring for pump head
Ø 95mm
606/15

spare part



o-ring 40mm
174-40

spare part



o-ring 50mm
174-50

spare part // optional



rotor complete 150/230W
FLOW version
606/20

For more information, please visit www.royal-exclusiv.de. Simply enter the part number or name into the search box or email: info@royal-exclusiv.de.

All information subject to change. We try our best, but printing errors reserved.