

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product form : Mixture

Product name : CITRUS MAGIC CLEANER

Product code : GT12801,05,15,55

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Multi-purpose cleaner and degreaser.

1.3. Details of the supplier of the safety data sheet

Gliptone Manufacturing Inc. 1740 Julia Goldbach Avenue

Ronkonkoma, NY 11779 - United States of America

T 1-631-285-7250 - F 1-631-589-5487

www.gliptone.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 International: 1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3 H226 - Flammable liquid and vapour Acute Tox. 4 (Oral) H302 - Harmful if swallowed Acute Tox. 4 (Dermal) H312 - Harmful in contact with skin H315 - Causes skin irritation

Skin Sens. 1 H317 - May cause an allergic skin reaction

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02 GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H302+H312 - Harmful if swallowed or in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 - Keep container tightly closed P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash ... thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P312 - If swallowed: Call a poison center/doctor/... if you feel unwell

P302+P352 - If on skin: Wash with plenty of water/...

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P312 - Call a poison center/doctor/... if you feel unwell P321 - Specific treatment (see ... on this label)

P330 - Rinse mouth

P332+P313 - If skin irritation occurs: Get medical advice/attention P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P363 - Wash contaminated clothing before reuse

05/01/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P370+P378 - In case of fire: Use ... to extinguish P403+P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%	Classification (GHS-US)
butyl glycolether	(CAS No) 111-76-2	5 - 40	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
(+)-limonene	(CAS No) 5989-27-5	5 - 20	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Artificial respiration and/or oxygen if necessary. Obtain medical attention.

First-aid measures after skin contact

Remove/Take off immediately all contaminated clothing. Immediately flush skin with plenty of water for at least 15 minutes. Obtain medical attention. Wash clothing before re-using.

First-aid measures after eye contact

Immediately flush eyes thoroughly with water for at least 15 minutes. Obtain medical attention.

First-aid measures after ingestion

Never give anything by mouth to an unconscious person. Symptoms are among other things headache, dizziness, dullness, muscular asthenia etc. Do NOT induce vomiting. Rinse mouth out with water. Drink two glasses of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

5.2. Special hazards arising from the substance or mixture

Fire hazard

Reactivity

: Flammable liquid and vapor. Keep away from heat, sparks and flame. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Under fire conditions closed containers may rupture or explode. Form with air vapors (heavier than air) who stay on the floor.

Explosion hazard

: Keep away from ignition sources (including static discharges).

: Flammable liquid and vapor.

Advice for firefighters

Firefighting instructions

: Move containers away from the fire area if this can be done without risk. Cool down the containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact between the water and the product.

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Other information

: On combustion forms: Carbon oxides (CO, CO2). Nitrogen oxides. irritating fumes.

05/01/2020 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Use protective clothing.

Emergency procedures : NO open flames, NO sparks, and NO smoking. Avoid contact with skin, eyes and clothing.

Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8 Exposure controls/personal protection" ".

Emergency procedures : Keep public away.

6.2. Environmental precautions

Avoid release to the environment. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters. Eliminate ignition sources. Ventilate well. Stop leak without risks if possible.

Other information : Dispose of materials or solid residues at an authorized site. Notify environmental authorities.

6.4. Reference to other sections

For further information refer to section 8: Exposure-controls/personal protection"".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Combustible liquid. TOXIC LIQUID, ORGANIC, N.O.S.

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the

container. Do not get in eyes, on skin, or on clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Use chemically protective clothing.

Safe use of the product : Keep away from (strong) bases. Keep container closed when not in use.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Avoid inhalation of vapors. Wash hands immediately after handling

the product. Wash clothing before re-using.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. No smoking. Inspect

frequently to identify any sing of warping or leak of the containers.

Special rules on packaging : Always keep in containers made of the same material as the supply container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butyl glycolether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time- weighted average exposure limit 8 h; TLV - Adopted Value)

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection : Impermeable protective gloves. Wear long sleeves. Use protective clothing.

Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls : Avoid release to the environment.

Other information : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure.

05/01/2020 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Colorless to light yellow
Odor : Lemon Citrus odor
Odor threshold : No data available

pH : 9.5

Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available

Flash point : 123 °F

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : 0.7 - 6

Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Vapor pressure : No data available

Relative density : 0.96
Relative vapor density at 20 °C : 4.7

Solubility : soluble in water.

Log Pow : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

9.2. Other information

VOC content : < 4 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin contact.; Eyes contact.; Inhalation; Ingestion.

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin.

CITRUS MAGIC CLEANER	
ATE US (oral)	1250.000 mg/kg body weight
ATE US (dermal)	1087.500 mg/kg body weight

05/01/2020 EN (English US) 4/8

Safety Data Sheet

butyl glycolether (111-76-2)	
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 43 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
ATE US (oral)	500.000 mg/kg body weight
ATE US (dermal)	435.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	2.170 mg/l/4h
ATE US (dust, mist)	2.170 mg/l/4h
(+)-limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
ATE US (oral)	4400.000 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
	pH: 9.5
Serious eye damage/irritation	: Not classified
	pH: 9.5
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
butyl glycolether (111-76-2)	
IARC group	3 - Not Classifiable
(+)-limonene (5989-27-5)	
IARC group	3 - Not Classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
promote surger organication, (emigro orpostation)	
Specific target organ toxicity (repeated exposure)	: Not classified
aspiration hazard	: Not classified
Symptoms/injuries after skin contact	: Irritation. May cause an allergic skin reaction.
Other information	: CNS depression.
SECTION 12: Ecological information	
2.1. Toxicity	
-cology - general	The product is not considered harmful to aquatic organisms nor to cause long-term adverse

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse Ecology - general effects in the environment. Do not allow into drains or water courses or dispose of where

ground or surface waters may be affected.

(+)-limonene (5989-27-5)	
LC50 fish 1	720 µg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	0.36 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	150 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Read-across)

Persistence and degradability 12.2.

butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.20 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance

05/01/2020 EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)		
BOD (% of ThOD)	0.31	
(+)-limonene (5989-27-5)		
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.	
ThOD	3.29 g O₂/g substance	

12.3. Bioaccumulative potential

butyl glycolether (111-76-2)		
Log Pow	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
(+)-limonene (5989-27-5)		
BCF fish 1	864.8 - 1022 (BCF; Pisces)	
Log Pow	4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C)	
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).	

12.4. Mobility in soil

butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
(+)-limonene (5989-27-5)	
(+)-limonene (5989-27-5)	

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s., 3, III

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Hazard Classes (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

3

Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

05/01/2020 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

During the transition period (June 2015-June 2017), Canadian regulation requires that the supplier must provide a document that conforms to either *Controlled Products Regulations* (WHMIS 1988) or HPR (WHMIS 2015), and not a combination of both. This document conforms to the post June 2017 HPR (WHMIS 2015) for a specific controlled or hazardous product. The classification, label and (material) SDS fully complies with the specific regulation chosen by the supplier.

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

05/01/2020 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Acute toxicity (dermal) Category 3
Acute toxicity (dermal) Category 4
Acute toxicity (inhalation) Category 4
Acute toxicity (oral) Category 4
Hazardous to the aquatic environment - Acute Hazard Category 1
Hazardous to the aquatic environment - Chronic Hazard Category 1
Flammable liquids Category 3
Flammable liquids Category 4
Skin corrosion/irritation Category 2
Skin sensitization Category 1
Flammable liquid and vapor
Combustible liquid
Harmful if swallowed
Toxic in contact with skin
Harmful in contact with skin
Causes skin irritation
May cause an allergic skin reaction
Harmful if inhaled
Very toxic to aquatic life
Very toxic to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

: 2 - Must be moderately heated or exposed to relatively high NFPA fire hazard

temperature before ignition can occur.

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with

some release of energy, but not violently.

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient Flammability

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high Physical

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

ACGIH: American Conference of Governmental Industrial Hygienists Legend:

NIOSH: National Institute of Occupational Safety and Health

CAS: Chemical Abstract Services DOT: Department of Transportation

HMIS: Hazardous Materials Identification System PEL: Permissible Exposure Limit

IARC: International Agency for Research on Cancer N/Av: not available

OSHA: Occupational Safety and Health Administration

SARA: Superfund Amendments & Reauthorization Act

CFR: Code of Federal Regulations EPA: Environmental Protection Agency

N/Ap: not applicable

NFPA: National Fire Protection Association

STEL: Short Term Exposure Limit TSCA: Toxic Substance Control Act TLV: Threshold Limit Values

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

05/01/2020 EN (English US) 8/8