

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Identification

Product form : Mixture

Product name : DRYING AGENT "CHERRY SCENTED"

Product code GT49205,30,55

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Drying Agent

Details of the supplier of the safety data sheet

Gliptone Manufacturing Inc. 1740 Julia Goldbach Avenue

Ronkonkoma, NY 11779 - United States of America

T 1-631-285-7250 - F 1-631-589-5487

www.gliptone.com

Emergency telephone number

Emergency number : 1-800-424-9300 International: 1-703-527-3887

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Classification (GHS-US)

H319 - Causes serious eye irritation Eye Irrit. 2A H317 - May cause an allergic skin reaction Skin Sens. 1 H351 - Suspected of causing cancer Carc. 2

Full text of H-phrases: see section 16

Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation H351 - Suspected of causing cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash ... thoroughly after handling

P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of water/...

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P321 - Specific treatment (see ... on this label)

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention

P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container to ...

Other hazards

No additional information available

2.4. **Unknown acute toxicity (GHS US)**

Not applicable

06/01/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%	Classification (GHS-US)
butyl glycolether	(CAS No) 111-76-2	0.5 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Trade Secret*	(CAS No) Trade Secret	1 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Carc. 2, H351 STOT SE 3, H336

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-phrases: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Obtain medical attention.

First-aid measures after skin contact Remove/Take off immediately all contaminated clothing. Wash skin thoroughly with mild soap

and water. Call a physician immediately. Wash clothing before re-using

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advice. First-aid measures after eye contact First-aid measures after ingestion

Do NOT induce vomiting. Obtain medical attention. Never give anything by mouth to an

unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool down the

containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact

between the water and the product.

Do not attempt to take action without suitable protective equipment. Self-contained breathing Protection during firefighting

apparatus. Complete protective clothing.

Other information Combustion produces irritating gases. Carbon oxides (CO, CO2). Silicon oxides.

Formaldehyde. Nitrogen oxides.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep public away.

6.1.1. For non-emergency personnel

Protective equipment : Use chemically protective clothing.

: Ventilate spillage area. NO open flames, NO sparks, and NO smoking. **Emergency procedures**

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8 Exposure controls/personal protection" ".

EN (English US) 06/01/2020 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: Exposure-controls/personal protection"".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : This product is hazardous. CORROSIVE LIQUID, N.O.S.

Precautions for safe handling : Ensure good ventilation of the work station. Avoid inhalation of vapors. Avoid contact with skin,

eyes and clothing. Keep container closed when not in use.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product. Wash clothing before re-using.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Special rules on packaging : Always keep in containers made of the same material as the supply container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butyl glycolether (111-7	76-2)	
ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-
		weighted average exposure limit 8 h; TLV - Adopted
		Value)

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection : Impermeable protective gloves. Wear long sleeves. Use protective clothing.

Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls : Avoid release to the environment.

Other information : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Clear red
Odor : Cherry

Odor threshold : No data available

pH : 6 - 8

Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available

Flash point : 94.4 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available Vapor pressure : No data available

06/01/2020 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density : 1.03

Relative vapor density at 20 °C : No data available

Solubility : In water, material is partially soluble.

Log Pow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Peroxides may be formed on prolonged contact with air.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Keep away from: strong acids, strong bases and oxidation agents.

10.6. Hazardous decomposition products

Aldehydes. Peroxides may be formed on prolonged contact with air.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin contact.; Eyes contact.; Inhalation; Ingestion.

Acute toxicity : Not classified

butyl glycolether (111-76-2)		
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)	
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)	
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)	
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence	
ATE US (oral)	500.000 mg/kg body weight	
ATE US (dermal)	435.000 mg/kg body weight	
ATE US (gases)	4500.000 ppmV/4h	
ATE US (vapors)	2.170 mg/l/4h	
ATE US (dust, mist)	2.170 mg/l/4h	
Trade Secret		

Trade Secret	
ATE US (oral)	373.832 mg/kg body weight
ATE US (dermal)	1087.500 mg/kg body weight

Skin corrosion/irritation : Not classified

pH: 6 - 8

Serious eye damage/irritation : Causes serious eye irritation.

pH: 6 - 8

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

06/01/2020 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
IARC group	3 - Not Classifiable

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Other information : CNS depression.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Do not discharge into drains or the environment. Do not discharge into surface water.

12.2. Persistence and degradability

butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O₂/g substance
Chemical oxygen demand (COD)	2.20 g O₂/g substance
ThOD	2.305 g O₂/g substance
BOD (% of ThOD)	0.31

12.3. Bioaccumulative potential

butyl glycolether (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated as dangerous goods or hazardous material.

TDG

Not regulated as dangerous goods or hazardous material.

Transport by sea

Not regulated as dangerous goods or hazardous material.

Air transport

Not regulated as dangerous goods or hazardous material.

06/01/2020 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Trade Secret CAS No 1 - 10%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-propanol CAS No 67-63-0 0.5 - 10%

15.2. International regulations

CANADA

During the transition period (June 2015-June 2017), Canadian regulation requires that the supplier must provide a document that conforms to either *Controlled Products Regulations* (WHMIS 1988) or HPR (WHMIS 2015), and not a combination of both. This document conforms to the post June 2017 HPR (WHMIS 2015) for a specific controlled or hazardous product. The classification, label and (material) SDS fully complies with the specific regulation chosen by the supplier.

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

butyl glycolether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

06/01/2020 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

: 1 - Must be preheated before ignition can occur. NFPA fire hazard

: 0 - Normally stable, even under fire exposure conditions, NFPA reactivity

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, Flammability

solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

STEL: Short Term Exposure Limit

TSCA: Toxic Substance Control Act

ACGIH: American Conference of Governmental Industrial Hygienists Legend:

NIOSH: National Institute of Occupational Safety and Health

CAS: Chemical Abstract Services CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System N/Ap: not applicable

IARC: International Agency for Research on Cancer NFPA: National Fire Protection Association PEL: Permissible Exposure Limit

N/Av: not available OSHA: Occupational Safety and Health Administration

SARA: Superfund Amendments & Reauthorization Act

TLV: Threshold Limit Values

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/01/2020 EN (English US) 7/7