

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

Identification

Product form : Mixture

Product name : EXTRA HEAVY BUFF CLEAR

Product code GT22001, 32

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Automobile polishing compound

Details of the supplier of the safety data sheet

Gliptone Manufacturing Inc. 1740 Julia Goldbach Avenue

Ronkonkoma, NY 11779 - United States of America

T 1-631-285-7250 - F 1-631-589-5487

www.gliptone.com

**Emergency telephone number** 

Emergency number : 1-800-424-9300 International: 1-703-527-3887

### SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

### Classification (GHS-US)

H227 - Combustible liquid Flam. Liq. 4

H340 - May cause genetic defects Muta. 1B

Carc. 1B H350 - May cause cancer Full text of H-phrases: see section 16

### Label elements

### **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H227 - Combustible liquid

H340 - May cause genetic defects

H350 - May cause cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308+P313 - If exposed or concerned: Get medical advice/attention

P370+P378 - In case of fire: Use ... to extinguish P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to ...

### Other hazards

No additional information available

#### **Unknown acute toxicity (GHS US)** 2.4.

Not applicable

### **SECTION 3: Composition/information on ingredients**

#### **Substance** 3.1.

Not applicable

#### 3.2. **Mixture**

06/01/2020 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
Heavy Alkylate Naphtha*	(CAS No) Trade Secret	1 - 20	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
distillates, hydrotreated light	(CAS No) 64742-47-8	1 - 20	Asp. Tox. 1, H304

<sup>\*</sup>Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-phrases: see section 16

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general

: IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If breathing stops, give artificial

Immediately flush eyes thoroughly with water for at least 15 minutes. Obtain medical attention.

respiration. Obtain medical attention.

First-aid measures after skin contact

Wash skin with plenty of water and soap. Remove contaminated clothes. Obtain medical attention. Wash clothing before re-using.

First-aid measures after eye contact
First-aid measures after ingestion

Do NOT induce vomiting. Obtain medical attention. Never give anything by mouth to an

unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media

: Dry powder. Foam. Carbon dioxide. Water fog.

Unsuitable extinguishing media

: Do not use a water jet since it may cause the fire to spread.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard

: Combustible product. Keep away from open flames, hot surfaces and sources of ignition. Exposure to fire may cause containers to rupture/explode. Will float and can be reignited on

water surface. Vapors may be heavier than air.

Explosion hazard

: Keep away from ignition sources (including static discharges).

Reactivity

: The product is non-reactive under normal conditions of use, storage and transport.

#### 5.3. Advice for firefighters

Firefighting instructions

: Move containers away from the fire area if this can be done without risk. Cool down the containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact between the water and the product.

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Special protective equipment for fire fighters

: Use chemically protective clothing.

Other information

: Combustion produces irritating gases. Carbon oxides (CO, CO2). Silicon oxides.

Formaldehyde. Nitrogen oxides.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep public away.

## 6.1.1. For non-emergency personnel

Protective equipment

: Use chemically protective clothing.

Emergency procedures

: NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection" ".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

06/01/2020 EN (English US) 2/6

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.3. Methods and material for containment and cleaning up

For containment : Eliminate ignition sources. Ensure adequate ventilation. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material. Cover spill with non combustible material, e.g.:

sand, earth, vermiculite. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection"".

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed

: Combustible product. Harmful liquid.

Precautions for safe handling

Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Provide local exhaust or general room ventilation. Floors, walls and

other surfaces in the hazard area must be cleaned regularly.

Safe use of the product

: Keep away from: strong oxidants. Keep container closed when not in use.

Hygiene measures

Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash clothing before

re-using.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a well-ventilated place. Keep cool. Store locked up. Keep away from heat and direct sunlight. Inspect frequently to identify any sing of warping or leak of the containers. No

smoking.

Special rules on packaging

: Always keep in containers made of the same material as the supply container.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Heavy Alkylate Naphtha		
ACGIH	ACGIH TWA (ppm)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	525 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection : Impermeable protective gloves. Wear long sleeves. Use protective clothing.

Eye protection : Safety glasses. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

Other information : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Thick Liquid

Color : Pale orange / Peach like, yellowish

Odor : Almost Odourless with slight alcohol and petroleum

Odor threshold : No data available

pH : 8 - 9.5

Melting point : Not applicable

Freezing point : No data available

Boiling point : No data available

Flash point : 77.8 °C

06/01/2020 EN (English US) 3/6

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available Vapor pressure : No data available

Relative density : 1.03

Relative vapor density at 20 °C : No data available Solubility : Partially soluble. : No data available Log Pow Auto-ignition temperature : No data available : No data available Decomposition temperature : No data available Viscosity Viscosity, kinematic : No data available : No data available Viscosity, dynamic

9.2. Other information

VOC content : < 10 %

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Respiratory or skin sensitization

Keep away from: strong acids, strong bases and oxidation agents.

### 10.6. Hazardous decomposition products

Aldehydes. ketones.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Likely routes of exposure : Skin contact.; Eyes contact.; Inhalation; Ingestion.

Acute toxicity : Not classified

Heavy Alkylate Naphtha		
LD50 oral rat	> 7000 mg/kg	
LD50 dermal rat	> 3000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	

Skin corrosion/irritation : Not classified pH: 8 - 9.5
Serious eye damage/irritation : Not classified

pH: 8 - 9.5 : Not classified

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer.

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

06/01/2020 EN (English US) 4/6

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Do not allow into drains or water courses or dispose of where

ground or surface waters may be affected.

### 12.2. Persistence and degradability

Heavy Alkylate Naphtha	
Persistence and degradability	No test data available. No (test)data on mobility of the substance available.

### 12.3. Bioaccumulative potential

Heavy Alkylate Naphtha	
Bioaccumulative potential	No test data available.

#### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

### **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Not regulated as dangerous goods or hazardous material.

### **TDG**

Not regulated as dangerous goods or hazardous material.

### Transport by sea

Not regulated as dangerous goods or hazardous material.

#### Air transport

Not regulated as dangerous goods or hazardous material.

# **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

aluminium oxide, activated CAS No 1344-28-1 10 - 40%

### 15.2. International regulations

### CANADA

During the transition period (June 2015-June 2017), Canadian regulation requires that the supplier must provide a document that conforms to either *Controlled Products Regulations* (WHMIS 1988) or HPR (WHMIS 2015), and not a combination of both. This document conforms to the post June 2017 HPR (WHMIS 2015) for a specific controlled or hazardous product. The classification, label and (material) SDS fully complies with the specific regulation chosen by the supplier.

06/01/2020 EN (English US) 5/6

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

### **SECTION 16: Other information**

#### Full text of H-phrases:

at of the principles.		
Asp. Tox. 1	Aspiration hazard Category 1	
Carc. 1B	Carcinogenicity Category 1B	
Flam. Liq. 3	Flammable liquids Category 3	
Flam. Liq. 4	Flammable liquids Category 4	
Muta. 1B	Germ cell mutagenicity Category 1B	
H226	Flammable liquid and vapor	
H227	Combustible liquid	
H304	May be fatal if swallowed and enters airways	
H340	May cause genetic defects	
H350	May cause cancer	

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high

temperature before ignition can occur.

1 - Normally stable, but can become unstable at elevated NFPA reactivity

temperatures and pressures or may react with water with

some release of energy, but not violently.

HMIS III Rating

: 2 Moderate Hazard - Temporary or minor injury may occur Health

: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient Flammability

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

ACGIH: American Conference of Governmental Industrial Hygienists Legend:

NIOSH: National Institute of Occupational Safety and Health

CAS: Chemical Abstract Services CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System N/Ap: not applicable IARC: International Agency for Research on Cancer

NFPA: National Fire Protection Association N/Av: not available PEL: Permissible Exposure Limit

OSHA: Occupational Safety and Health Administration STEL: Short Term Exposure Limit SARA: Superfund Amendments & Reauthorization Act TSCA: Toxic Substance Control Act TLV: Threshold Limit Values

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/01/2020 EN (English US) 6/6