

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product form : Mixture
Product name : GT SURFACE CLENZ
Product code : GT19502, GT19532, GT19501, GT19505

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Hard surface cleaner

1.3. Details of the supplier of the safety data sheet

Gliptone Manufacturing Inc.
1740 Julia Goldbach Avenue
Ronkonkoma, NY 11779 - United States of America
T 1-631-285-7250 - F 1-631-589-5487
www.gliptone.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 International: 1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225 - Highly flammable liquid and vapour

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor
Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P370+P378 - In case of fire: Use ... to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

GT SURFACE CLENZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
2-propanol	(CAS No) 67-63-0	20 - 65	Flam. Liq. 2, H225 STOT SE 3, H336

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash off immediately and plentifully with water for at least 20 minutes. Call a physician immediately. Wash clothing before re-using.
- First-aid measures after eye contact : Rinse thoroughly with plenty of water for at least 20 minutes and take medical advice.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain medical attention. Never give anything by mouth to an unconscious person. Drink two glasses of water.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor. Under fire conditions closed containers may rupture or explode. Keep away from open flames, hot surfaces and sources of ignition. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
- Explosion hazard : Keep away from ignition sources (including static discharges).
- Reactivity : Highly flammable liquid and vapor.

5.3. Advice for firefighters

- Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool down the containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact between the water and the product.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : Combustion produces irritating gases. Carbon oxides (CO, CO₂). Nitrogen oxides. Phosphorous oxide.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep public away.

6.1.1. For non-emergency personnel

- Protective equipment : Use chemically protective clothing.
- Emergency procedures : Ventilate spillage area. NO open flames, NO sparks, and NO smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection" .

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

- For containment : Eliminate ignition sources. Ensure adequate ventilation. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

GT SURFACE CLENZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Flammable liquids.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep away from (strong) acids. Keep container closed when not in use.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Avoid contact with skin, eyes and clothing. Wash clothing before re-using.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up. Inspect frequently to identify any sign of warping or leak of the containers. No smoking.
- Special rules on packaging : Always keep in containers made of the same material as the supply container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-propanol (67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm (2-propanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	400 ppm (2-propanol; USA; Short time value; TLV - Adopted Value)
OSHA	OSHA PEL (STEL) (mg/m ³)	1225 mg/m ³
OSHA	OSHA PEL (STEL) (ppm)	500 ppm

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Hand protection : Impermeable protective gloves. Wear long sleeves. Use protective clothing.
- Eye protection : Safety glasses. Contact lenses should not be worn.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Environmental exposure controls : Avoid release to the environment.
- Other information : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Mixture contains one or more component(s) which have the following colour(s):
Colourless
- Odor : Mixture contains one or more component(s) which have the following odour(s):
Alcohol odour
- Odor threshold : No data available
- pH : No data available
- Melting point : Not applicable
- Freezing point : No data available
- Boiling point : No data available
- Flash point : 18°C
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available

GT SURFACE CLENZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

VOC content : < 20 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Keep away from: oxidants, strong acids and strong bases. alkaline metals.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin contact.; Eyes contact.; Inhalation; Ingestion.

Acute toxicity : Not classified

2-propanol (67-63-0)	
LD50 oral rat	5045 mg/kg
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	8000 ppm/4h
ATE US (oral)	5045.000 mg/kg body weight
ATE US (dermal)	12870.000 mg/kg body weight
ATE US (gases)	8000.000 ppmV/4h
ATE US (vapors)	73.000 mg/l/4h
ATE US (dust, mist)	73.000 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

2-propanol (67-63-0)	
IARC group	3 - Not Classifiable

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

GT SURFACE CLENZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Other information	: CNS depression.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Do not discharge into drains or the environment. Do not discharge into surface water. Not harmful to aquatic organisms.

2-propanol (67-63-0)	
LC50 fish 2	9640 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 2	13299 mg/l (EC50; Other; 48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (EC50; UBA; 72 h; Scenedesmus subspicatus)

12.2. Persistence and degradability

2-propanol (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.40 g O ₂ /g substance

12.3. Bioaccumulative potential

2-propanol (67-63-0)	
Log Pow	0.05 (Weight of evidence approach; Other; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

2-propanol (67-63-0)	
Surface tension	0.021 N/m (25 °C)

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1219 Isopropanol, 3, II
UN-No.(DOT) : UN1219
Proper Shipping Name (DOT) : Isopropanol
Hazard Classes (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

GT SURFACE CLENZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 4b;150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Other information	: No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG)	: 1219
Proper Shipping Name (IMDG)	: ISOPROPANOL (ISOPROPYL ALCOHOL)
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

Air transport

UN-No.(IATA)	: 1219
Proper Shipping Name (IATA)	: ISOPROPYL ALCOHOL
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-propanol	CAS No 67-63-0	20 - 65%
2-propanol (67-63-0)		
Listed on SARA Section 313 (Specific toxic chemical listings)		

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

GT SURFACE CLENZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-propanol (67-63-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Full text of H-phrases:

Flam. Liq. 2	Flammable liquids Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H336	May cause drowsiness or dizziness

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product