

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Identification

Product form : Mixture

Product name : HEAVY DUTY BLUE MULTI-PURPOSE CLEANER

Product code : GT40505,15,30,55

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Multi purpose cleaner

Details of the supplier of the safety data sheet

Gliptone Manufacturing Inc. 1740 Julia Goldbach Avenue

Ronkonkoma, NY 11779 - United States of America

T 1-631-285-7250 - F 1-631-589-5487

www.gliptone.com

Emergency telephone number

Emergency number : 1-800-424-9300 International: 1-703-527-3887

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Classification (GHS-US)

H315 - Causes skin irritation Skin Irrit. 2 H318 - Causes serious eye damage Eye Dam. 1

Full text of H-phrases: see section 16

Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H315 - Causes skin irritation

H318 - Causes serious eye damage

Precautionary statements (GHS-US) : P264 - Wash ... thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of water/...

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center/doctor/... P321 - Specific treatment (see ... on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

Other hazards

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substance

Not applicable

06/01/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
butyl glycolether	(CAS No) 111-76-2	2 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
sodium hydroxide	(CAS No) 1310-73-2	1 - 5	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
disodium metasilicate	(CAS No) 6834-92-0	1 - 5	Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give

oxygen. If breathing stops, give artificial respiration. Obtain medical attention.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse immediately with plenty of water for 15 minutes. Obtain medical attention. Wash clothing before re-using.

First-aid measures after eye contact : Wash immediately with plenty water (during 20 minutes), also under eyelids. Obtain medical

attention

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth out with water. Drink two glasses of water. Obtain medical

attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Irritation to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable. Under fire conditions closed containers may rupture or explode.

5.3. Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool down the

containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact

between the water and the product.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

Other information : Combustion generates : Carbon oxides (CO, CO2). Phosphorous oxide. Hydrogen sulfide.

irritating fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep public away.

6.1.1. For non-emergency personnel

Protective equipment : Use chemically protective clothing.

Emergency procedures : Ventilate spillage area. NO open flames, NO sparks, and NO smoking. Avoid contact with skin

and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8 Exposure controls/personal protection" ".

6.2. Environmental precautions

Avoid release to the environment. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

06/01/2020 EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Ventilate well. Stop leak without risks if possible. Take up liquid spill into inert absorbent material. Notify authorities if product enters sewers or public waters. Notify environmental

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection"".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: TOXIC LIQUID, ORGANIC, N.O.S. Use chemically protective clothing. Store in well ventilated area. Avoid inhalation of vapors. Avoid contact with skin, eyes and clothing. Keep away from oxidizing agents. Keep container closed when not in use.

Precautions for safe handling

Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep container closed when not in use.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. No smoking. Inspect

frequently to identify any sing of warping or leak of the containers.

Special rules on packaging

: Always keep in containers made of the same material as the supply container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters butyl glycolether (111-76-2)

ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time- weighted average exposure limit 8 h; TLV - Adopted
sodium hydroxide (1310-7	3-2)	Value)
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
ACGIH	Remark (ACGIH)	URT, eye, & skin irr
OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Materials for protective clothing : Wear long sleeves.

Hand protection : Impermeable protective gloves.

Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls : Avoid release to the environment.

Other information : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color : Blue

Odor : Irritating/pungent odor
Odor threshold : No data available
pH : No data available

pH solution : 10

06/01/2020 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point : Not applicable
Freezing point : No data available
Boiling point : > 100 °C
Flash point : 98 °C

: No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : No data available : No data available **Explosion limits** Explosive properties : No data available Oxidizing properties : No data available Vapor pressure < 20 mm Hg Relative density : 1.04 Relative vapor density at 20 °C : < 1

Solubility : soluble in water.

Log Pow : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

9.2. Other information

VOC content : < 5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Keep away from: strong oxidants.

10.6. Hazardous decomposition products

Sodium ions and Silicic acid.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin contact.; Eyes contact.; Inhalation; Ingestion.

Acute toxicity : Not classified

outyl glycolether (111-76-2)	
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
ATE US (oral)	500.000 mg/kg body weight
ATE US (dermal)	435.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	2.170 mg/l/4h
ATE US (dust, mist)	2.170 mg/l/4h

06/01/2020 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 56 / Monday, March 26, 2012 / Rules and Regulations		
disodium metasilicate (6834-92-0)		
> 5000 mg/kg body weight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)		
: Causes skin irritation.		
: Causes serious eye damage.		
: Not classified		
: Not classified		
: Not classified		
3 - Not Classifiable		
: Not classified		
: Not classified		

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Irritation to eyes.

Other information : CNS depression.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment. Do not discharge into drains or the environment.

sodium hydroxide (1310-73-2)		
LC50 fish 1	45.4 mg/l (LC50; Other; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)	
disodium metasilicate (6834-92-0)		
LC50 fish 1	210 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)	
Threshold limit algae 1	207 mg/l (EC50; DIN 38412-9; 72 h; Scenedesmus subspicatus; Fresh water)	

12.2. Persistence and degradability

butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.20 g O ₂ /g substance	
ThOD	2.305 g O ₂ /g substance	
BOD (% of ThOD)	0.31	
sodium hydroxide (1310-73-2)		
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
disodium metasilicate (6834-92-0)		
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	

12.3. Bioaccumulative potential

butyl glycolether (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

06/01/2020 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

sodium hydroxide (1310-73-2)	
Bioaccumulative potential	No bioaccumulation data available.
disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated as dangerous goods or hazardous material.

TDG

Not regulated as dangerous goods or hazardous material.

Transport by sea

Not regulated as dangerous goods or hazardous material.

Air transport

Not regulated as dangerous goods or hazardous material.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

	sodium hydroxide (1310-73-2)	
Not listed on SARA Section 313 (Specific toxic chemical listings)		
	RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb

15.2. International regulations

CANADA

During the transition period (June 2015-June 2017), Canadian regulation requires that the supplier must provide a document that conforms to either *Controlled Products Regulations* (WHMIS 1988) or HPR (WHMIS 2015), and not a combination of both. This document conforms to the post June 2017 HPR (WHMIS 2015) for a specific controlled or hazardous product. The classification, label and (material) SDS fully complies with the specific regulation chosen by the supplier.

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

06/01/2020 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

butyl glycolether (111-76-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

sodium hydroxide (1310-73-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Acute toxicity (dermal) Category 3
Acute toxicity (inhalation) Category 4
Acute toxicity (oral) Category 4
Serious eye damage/eye irritation Category 1
Flammable liquids Category 4
Corrosive to metals Category 1
Skin corrosion/irritation Category 1A
Skin corrosion/irritation Category 2
Specific target organ toxicity (single exposure) Category 3
Combustible liquid
May be corrosive to metals
Harmful if swallowed
Toxic in contact with skin
Causes severe skin burns and eye damage
Causes skin irritation
Causes serious eye damage
Harmful if inhaled
May cause respiratory irritation

NFPA health hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

: 1 - Normally stable, but can become unstable at elevated NFPA reactivity

temperatures and pressures or may react with water with

some release of energy, but not violently.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high **Physical**

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

ACGIH: American Conference of Governmental Industrial Hygienists Legend:

NIOSH: National Institute of Occupational Safety and Health

CAS: Chemical Abstract Services CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System N/Ap: not applicable NFPA: National Fire Protection Association

IARC: International Agency for Research on Cancer

N/Av: not available PEL: Permissible Exposure Limit OSHA: Occupational Safety and Health Administration STEL: Short Term Exposure Limit SARA: Superfund Amendments & Reauthorization Act TSCA: Toxic Substance Control Act

TLV: Threshold Limit Values

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/01/2020 EN (English US) 7/7