

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Identification

Product form : Mixture  
Product name : PURPLE MAXX  
Product code : GT44101, GT44105, GT44155

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Heavy Duty Degreaser

#### 1.3. Details of the supplier of the safety data sheet

Gliptone Manufacturing Inc.  
1740 Julia Goldbach Avenue  
Ronkonkoma, NY 11779 - United States of America  
T 1-631-285-7250 - F 1-631-589-5487  
[www.gliptone.com](http://www.gliptone.com)

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300 International: 1-703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Skin Corr. 1A H314 - Causes severe skin burns and eye damage

Eye Dam. 1 H318 - Causes serious eye damage

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage  
Precautionary statements (GHS-US) : P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P264 - Wash ... thoroughly after handling  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a poison center/doctor/...  
P321 - Specific treatment (see ... on this label)  
P363 - Wash contaminated clothing before reuse  
P405 - Store locked up  
P501 - Dispose of contents/container to ...

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
butyl glycoether	(CAS No) 111-76-2	2 - 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
SURFACTANT GROUP	(CAS No) 68439-46-3	2 - 20	Acute Tox. 4 (Oral), H302
2-aminoethanol	(CAS No) 141-43-5	1 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318
sodium hydroxide	(CAS No) 1310-73-2	1 - 5	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318

Full text of H-phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash off immediately and plentifully with water for at least 20 minutes. Wash clothing before re-using. Obtain medical attention.
- First-aid measures after eye contact : Rinse thoroughly with plenty of water for at least 20 minutes and take medical advice.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain medical attention. Never give anything by mouth to an unconscious person. Drink two glasses of water.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Burns.
- Symptoms/injuries after eye contact : Serious damage to eyes.
- Symptoms/injuries after ingestion : Burns.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable. Under fire conditions closed containers may rupture or explode. Attacks light metals(Al, Zn) releasing hydrogen gas.
- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

#### 5.3. Advice for firefighters

- Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool down the containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact between the water and the product.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : Combustion produces irritating gases. Carbon oxides (CO, CO<sub>2</sub>).

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep public away.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Use chemically protective clothing.
- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses.

### 6.3. Methods and material for containment and cleaning up

For containment : Eliminate ignition sources. Ensure adequate ventilation. Stop leak without risks if possible.  
Methods for cleaning up : Take up liquid spill into inert absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : CORROSIVE LIQUID, TOXIC, N.O.S.  
Precautions for safe handling : Ensure good ventilation of the work station. Keep away from : acids. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up. Inspect frequently to identify any sing of warping or leak of the containers. No smoking.  
Special rules on packaging : Always keep in containers made of the same material as the supply container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

butyl glycolether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

sodium hydroxide (1310-73-2)		
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	URT, eye, & skin irr
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

2-aminoethanol (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm (Ethanalamine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	6 ppm (Ethanalamine; USA; Short time value; TLV - Adopted Value)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	3 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Hand protection : Impermeable protective gloves. Wear long sleeves. Use protective clothing.  
Eye protection : Safety glasses. Contact lenses should not be worn.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.  
Environmental exposure controls : Avoid release to the environment.  
Other information : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following colour(s): Purple
Odor	: Mixture contains one or more component(s) which have the following odour(s): Detergent
Odor threshold	: No data available
pH	: 12.5 - 13
Melting point	: Not applicable
Freezing point	: 0 °C
Boiling point	: 100 °C
Flash point	: 98 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: 1.04
Relative vapor density at 20 °C	: No data available
Solubility	: soluble in water. Water: Solubility in water of component(s) of the mixture : • butyl glycoether: Complete • sodium hydroxide: 42 g/100ml • 2-aminoethanol: Complete
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces.

#### 10.5. Incompatible materials

Keep away from: strong oxidants.

#### 10.6. Hazardous decomposition products

No additional information available

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Likely routes of exposure	: Skin contact.; Eyes contact.; Inhalation; Ingestion.
Acute toxicity	: Not classified

# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>butyl glycolether (111-76-2)</b>	
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
ATE US (oral)	500.000 mg/kg body weight
ATE US (dermal)	435.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	2.170 mg/l/4h
ATE US (dust, mist)	2.170 mg/l/4h

<b>SURFACTANT GROUP (68439-46-3)</b>	
LD50 oral rat	1378 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
ATE US (oral)	1378.000 mg/kg body weight

<b>2-aminoethanol (141-43-5)</b>	
LD50 oral rat	1720 mg/kg (Rat)
LD50 dermal rabbit	1018 mg/kg (Rabbit)
ATE US (oral)	1720.000 mg/kg body weight
ATE US (dermal)	1018.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 12.5 - 13
Serious eye damage/irritation	: Causes serious eye damage. pH: 12.5 - 13
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>butyl glycolether (111-76-2)</b>	
IARC group	3 - Not Classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after skin contact	: Burns.
Symptoms/injuries after eye contact	: Serious damage to eyes.
Symptoms/injuries after ingestion	: Burns.
Other information	: CNS depression.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Do not discharge into drains or the environment. Do not discharge into surface water.
-------------------	---

<b>sodium hydroxide (1310-73-2)</b>	
LC50 fish 1	45.4 mg/l (LC50; Other; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)

# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-aminoethanol (141-43-5)</b>	
LC50 fish 1	150 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 1	140 mg/l (EC50; 24 h)
Threshold limit algae 2	35 mg/l (EC50; 72 h)

### 12.2. Persistence and degradability

<b>butyl glycoether (111-76-2)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.20 g O <sub>2</sub> /g substance
ThOD	2.305 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.31

<b>SURFACTANT GROUP (68439-46-3)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>sodium hydroxide (1310-73-2)</b>	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

<b>2-aminoethanol (141-43-5)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.80 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.34 g O <sub>2</sub> /g substance
ThOD	2.49 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.32

### 12.3. Bioaccumulative potential

<b>butyl glycoether (111-76-2)</b>	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>SURFACTANT GROUP (68439-46-3)</b>	
Bioaccumulative potential	No bioaccumulation data available.

<b>sodium hydroxide (1310-73-2)</b>	
Bioaccumulative potential	No bioaccumulation data available.

<b>2-aminoethanol (141-43-5)</b>	
Log Pow	-1.91
Bioaccumulative potential	Bioaccumulation: not applicable.

### 12.4. Mobility in soil

<b>butyl glycoether (111-76-2)</b>	
Surface tension	0.027 N/m (25 °C)

<b>2-aminoethanol (141-43-5)</b>	
Surface tension	0.050 N/m

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1824 Sodium hydroxide solution, 8, III

UN-No.(DOT) : UN1824

Proper Shipping Name (DOT) : Sodium hydroxide solution

Hazard Classes (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Other information : No supplementary information available.

#### TDG

No additional information available

#### Transport by sea

UN-No. (IMDG) : 1824

Proper Shipping Name (IMDG) : SODIUM HYDROXIDE SOLUTION

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : III - substances presenting low danger

#### Air transport

UN-No.(IATA) : 1824

Proper Shipping Name (IATA) : SODIUM HYDROXIDE SOLUTION

Class (IATA) : 8 - Corrosives

Packing group (IATA) : III - Minor Danger

# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### **SURFACTANT GROUP (68439-46-3)**

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).

#### **sodium hydroxide (1310-73-2)**

Not listed on SARA Section 313 (Specific toxic chemical listings)

RQ (Reportable quantity, section 304 of EPA's List of Lists)

1000 lb

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

##### National regulations

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

#### **butyl glycoether (111-76-2)**

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### **sodium hydroxide (1310-73-2)**

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### **2-aminoethanol (141-43-5)**

U.S. - New Jersey - Right to Know Hazardous Substance List



# PURPLE MAXX

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H332	Harmful if inhaled

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*