



Color: Black-White

UPC Code: 078477808290

Country Of Origin: Mexico

**Available Colors:** 



# 2413

Locking Connector, 20 Amp, 125/250 Volt, Industrial Grade, Black & White

20 Amp, 125/250 Volt, NEMA L14-20R, 3P, 4W, Locking Connector, Industrial Grade, Grounding - BLACK-WHITE

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty

#### **Technical Information**

**Electrical Specifications Environmental Specifications** 

Amperage: 20 A **Environment**: Dry

**Current Interrupting:** Certified Flammability: Rated HB or for current interrupting at full better UL94 rated current

Operating Temperature: -40° C to 60°C Dielectric Voltage:

Withstands 2000V per UL498

**Grounding:** Grounding

**Pole**: 3

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125/250 VAC

Wire: 4

Material Specifications Mechanical Specifications

Assembly Screws: Steel, Zinc At Rated Voltage: 2 HP L-L/

Plated 1 HP L-N

**Back Cover:** Thermoplastic

Blades/Contacts: Solid Brass

**Body Material: Impact** 

Modified Nylon

Clamp Insert: Nylon

Color: Black-White

Cord-Clamp: Nylon

Terminal Screws: Brass

Wire Module: Nylon

Cord Range: 0.560 to 0.775

Product ID: Ratings are permanently marked on device

Terminal Accom.: 18-10 AWG

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Torque Range: 10-14 in-lbs

Wire Gauge: 14-10 AWG

**Product Features** 

Brand: Black and White

Color: Black-White

Device Type: Locking

Connector

**NEMA:** L14-20R

Standards and Certifications

**ANSI:** C-73

CSA C22.2 No. 42 : File LR-406

NEMA: WD-6

**NOM:** 057

UL Fed Spec WC-596: File

E13393


UL498: File E13393


Warranty: Limited Lifetime

Warranty

## Wiring Diagram

## **Dimensional Drawing**





### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

## Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:  $\underline{\text{www.leviton.com/company/about-leviton/locations}}$ 

## © 2025 Leviton Manufacturing Co., Inc.