



2440

20 Amp, 120/208 Volt, Flush Mount Locking Receptacle,
Industrial Grade

20 Amp, 120/208 Volt 3-Phase Y, NEMA L18-20R, 4P, 4W, Flush
Mtg Locking Receptacle, Industrial Grade, Non-Grounding, V-0-
MAX - BLACK

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

UPC Code : 078477045343

Country Of Origin : Mexico

NEMA :  L18-20R

Technical Information

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated
Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Non-Grounding

Phase : 3-Phase WYE

Pole : 4

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 120/208 VAC

Wire : 4

Environmental Specifications

Environment : Corrosive

Flammability : Rated V-0 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Base Material : Valox

Body Material : Nylon

Color : Black

Cover Material : Valox 357

Face Material : Ultramid

Ground Contacts : Brass

Grounding Screw :
Chromated Brass

Line Contacts : Brass

Strap Material : Nickel-Plated
Brass

Terminal Clamps : Nickel-
Plated Brass

Terminal Screws : Chromated
Brass

Mechanical Specifications

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 14-8 AWG

Terminal ID : Marked on Device

Termination : Back & Side

Product Features

Base Material : Valox

Brand : V-0-Max

Color : Black

Device Type : Locking
Receptacle

Face Material : Ultramid

NEMA : L18-20R

Voltage : 120/208 VAC

Warranty : Limited Lifetime
Warranty

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-1 & WD-6


NOM : 057

UL : 498

UL Fed Spec : W-C-596

Warranty : Limited Lifetime
Warranty

Wiring Diagram



Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.