

27CM-10

30 Amp, 125/250 Volt, Flush Mount Locking Receptacle,
Corrosion Resistant, Industrial Grade

30 Amp, 125/250 Volt, NEMA L14-30R, 3P, 4W, Flush Mtg
Locking Receptacle, Industrial Grade, Grounding, Corrosion-
Resistant - YELLOW

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability. For use in marine and industrial environments.

UPC Code : 078477108185

Country Of Origin : Mexico

NEMA :  L14-30R

Technical Information

AC Horsepower Ratings

At Rated Voltage : 2 HP L-L /
2 HP L-N

Electrical Specifications

Amperage : 30 A

Current Limiting : Full Rated
Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 3

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125/250 VAC

Wire : 4

Environmental Specifications

Environment : Corrosive

Flammability : Rated V-0 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Base Material : Nylon

Body Material : Valox 357

Color : Yellow

Cover Material : Valox 357

Face Material : Nylon

Ground Contacts : Nickel-
Plated Brass

Grounding Screw :
Chromated Brass

Line Contacts : Nickel-Plated
Brass

Strap Material : Nickel-Plated
Brass

Terminal Clamps : Nickel-
Plated Brass

Terminal Screws : Nickel-Plated Brass

Mechanical Specifications

Product ID : Ratings and NEMA I.D. permanently marked on device

Screw Terminal Torque : 10-14 in-lbs

Terminal Accom. : 14-8 AWG

Terminal ID : Marked on Device

Termination : Back

Product Features

Base Material : Nylon

Brand : V-0-Max

Color : Yellow

Face Material : Nylon

NEMA : L14-30R

Termination : Back

Warranty : Limited Lifetime Warranty

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-1 & WD-6

NOM : 057


UL : 498

UL Fed Spec : W-C-596

Warranty

Warranty : Limited Lifetime Warranty

Wiring Diagram



Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.