




Color :  White

UPC Code : 078477723890

Country Of Origin : China

NEMA :  5-20R

Available Colors :



GFPL2-PLW

20 Amp SmartlockPro® GFCI Receptacle/Outlet with Pilot Light, Industrial Grade, Tamper-Resistant

SmartlockPro Self-Test GFCI Single Receptacle Outlet, Extra Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Pilot Light (Illuminated - ON) 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 20 A

Grounding : Self-Grounding

Pole : 2

Short Circuit Current Rating : 10kA

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -35C to +66C

Material Specifications

Body Material : Polycarbonate

Face Material : PBT

Ground Clips : Brass

Grounding Screw : Plated Steel

Line Contacts : Brass

Shutter Mechanism : Delrin® Acetal

Strap Material : Galvanized Steel

Terminal Clamp : Brass

Terminal Screws : Plated Steel

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-10 AWG solid or stranded

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Back or Side Wire

Product Features

Brand : SmartlockPro

Color : White

Device Type : Single Receptacle Outlet

Feature : Tamper-Resistant|Pilot Light (Illuminated ON)

Function : GFCI

Grade : Extra Heavy-Duty Industrial Specification Grade

NEMA : 5-20R

Trip Level : Class A, 5mA plus
or minus 1mA

Standards and Certifications

ANSI : C-73

Applicable Standards : UL
943, UL 498, CSA C22.2 No.
42 & 144, FedSpec W-C-596

Certification/Listing : UL,
CSA, NOM-ANCE

NEMA : WD-1 & WD-6

Warranty

Warranty : 2-Year Limited

Patents *

CA2621644	CA2677283
CA2865659	MX302458
MX308495	US7355117
US7697252	US7820909
US7868719	US8242362
US8587914	US8599522
US9053886	US9077091

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.