
SPECIFICATION



3000K-4000K-5000K **3CCT Changeable**

Flip the switch on the driver to change 3 CCT

















3CCT LED DIMMABLE DOWNLIGHT

NXCOB60-12W-3CCT-DIM

Specification

LED DOWNLIGHT PRODUCT NAME:

NXCOB60-12W-3CCT-DIM MODEL NO.:

AC100-120V, 50-60Hz, 0.3A max, 12W SPECIFICATION:

WORKING TEMP: -20-50(°C)

0.9 **POWER FACTOR:**

>80 CRI(RA):

COLOR: White/Black

COB LIGHT SOURCE:

>100 LM/W LUMEN:

38° **BEAM ANGLE:**

360° Gimbal ADJUSTABLE ANGLE:

PRODUCT SIZE: D4.88XH1.89 inch

Cutout 4.1/8 inch

Suitable for Damp location IP:

Home, shop, hotel..etc. **APPLICATION:**

WARRANTY: 5 years

STANDARD: ETL

3000K-4000K-5000K COLOR TEMP:

(Changeable Dimmable)





NEXLEDS LTD

Feature:

The design rights of the fixture as well as accessories belong solely to NEXLEDS LTD


- 1.cETLus safety standard certified.
- 2. Connection box is made of aluminum material.
- 3. Two quick connectors for easy installation.
- 4. Anti-glare design downlight
- 5. Excellent dimming effect, real 0-100% dimmable.
- 6.12 watts 1200 lumens with high brightness COB light source.
- 7. Professional neutral color box packaging.

Free Combination






Dimension:




Installation:

- 1.Cut off power before installation. Drill a hole on the ceiling. (Step 1)
- 2.Install the junction box, and connect the lamp driver. (Step 2)(Step 3)
- 3. Connect the lamp connectors and locked it with the DC end of the driver. (Step 4)
- 4. Fasten the clip to the ceiling. (Step 5)
- 5. Turn on the power to make sure the downlight is well installed.











Caution:

- 1.Confirm whether the package is complete or not before installation.
- 2.Led downlight should be driven by appointed power supply.
- 3. Keep away from supply before cleaning downlight.
- 4. Final interpretation is owned by NEXLEDS.

