

L-Shaped Fan & Fixture Mounting Boxes

Our lowest cost L-shaped fan/fixture boxes mount securely to single or double joists with a shipped in place center screw.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D
FB442	72194	For 1/2" or 5/8" drywall 13.4 cu. in.	25	25	4.236	3.773	4.250	3.273
FB443	72197	For 1/2" or 5/8" drywall 18.3 cu. in.	25	25	4.236	5.071	4.250	4.571



PATENTED.
MADE IN USA.

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes using the parked screws provided. Refer to chart on page R-25 for load ratings and number of single conductors.

FEATURES AND BENEFITS

- No loose parts to misplace, totally self contained!
- Fan/fixture installation screws are parked and ready for easy fan/fixture bracket installation!
- UL rated: 70 lb fan, 200 lb fixture; CSA rated: 50 lb fan/fixture
- Locator posts assure proper positioning of fan/fixture bracket
- Competitively priced
- 2 hour fire rating


FAN/FIXTURE BOX INCLUDES

A ready to tighten center screw, installed NM cable connector, mud cover, multiple KOs, and two screws for fan/fixture bracket installation (screwed in place until removed by installer).

INSTALLATION INSTRUCTIONS



1
Position box alongside joist. Tightening center screw will mount box to joist.



2
Position mounting bracket over locator posts to assure proper position. Pull wires through KO.



3
Remove captive bracket installation screws. Use them to mount fan/fixture bracket. (Installation of drywall not shown.)



Locator posts for positioning of bracket installation screws

