



# LBL-COB-280-24V-8MM-100FT-IP20

COB LED Strip 24V 1.5W/ft 100ft long 8mm wide IP20

Project:

Location:

Model # :

Qty:

Notes:

## DESCRIPTION

- COB LED 4 mm wide super flexible strip 24V for dry locations
- Seamless linear light - no diffused cover needed
- No hotspots and with CRI 90+ for vibrant colors
- Higher efficiency and more flexible than SMD LED strips
- Easy to install and low maintenance
- Double sided adhesive 3M tape and wires on both ends

## APPLICATIONS


- Cove and decorative lighting, path and contour marking
- Undercabinet and valance use

## INSTALLATION INSTRUCTIONS


1. Remove backing paper to reveal adhesive tape



2. Press LED tape firmly onto clean smooth surface that adsorbs heat, such as metal or glass. Start at one end and gradually move along surface, making sure tape is smooth and not creased



3. Cut on trim marks



## WARNING

LED tape gets hot. Mounting firmly and securely on smooth and thermo conductive surface such as metal or glass is critical for proper thermal management and long life.

Not following these instructions voids the warranty

## ORDERING GUIDE


2700K	LBL-COB-280-24V-8MM-27K-100FT-IP20
3000K	LBL-COB-280-24V-8MM-30K-100FT-IP20
4000K	LBL-COB-280-24V-8MM-40K-100FT-IP20

## SPECIFICATION (tolerance +/- 10%)

Applications	Undercabinet, Cove, Valance, Decorative
Color Temperature (K)	2700   3000   4000
Power	1.5 W/ft
Efficiency	65 lm/W
Light output	100 lm/ft
Length per roll	100 ft / 30 meters
Maximum Length	16.4 ft / 5 meters
Width	5/16" / 8 mm
Power per Max Length	25 W
Lumen per Max Length	1,650 lm
Beam Angle	180°
CRI	90 +
Input	24V DC
Dimmable	Yes
LED Operation Type	Constant Voltage
IP Grade	IP 20
Approved Location	Indoor / Dry Location
Ambient Temperature	-4°F (-20°C) to +104°F (+40°C)
Cuttable Increment	2"
LEDs density	280 LEDs / meter
Adhesive Tape Type	3M 300SE
Projected Life	70% Light Output at 20,000 Hours
Certification	cETLus
Warranty	3 Year

## ACCESSORIES


Sold Separately



Aluminum Channel 3.3 ft (1 m) long  
Silver with white diffuser model # **XC610**  
Black with black diffuser model # **XC610-BK**



Strip Connector 8mm no wires model # **LCS-0-8MM**  
Single Connector with 6" wire model # **LCS-1-8MM**  
Two Connectors with 6" wire model # **LCS-2-8MM**



[Tape to Wire Straight Screw Connector # SC-8-10-TW](#)

[Tape to Tape Straight Screw Connector # SC-8-10-TT-1](#)

[Tape to Tape 90° L-shape Screw Connector # SC-8-10-TT-9](#)

Note: All connectors fit inside the channel

## Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500  
Hainesport NJ, Naples FL, Vancouver WA

## [www.LotusLEDLights.com](http://www.LotusLEDLights.com)

mailing addresses  
warehouses

## Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6J6 tel 604-538-3090  
Delta BC & Mississauga ON