



Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 5-20R

By Hubbell Wiring Device-Kellems
Catalog # [2182LALTRA](#)

Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Light Almond

Features

- Tamper-resistant shutter complies with national electrical code requirements
- Triple wipe contacts
- High impact resistant decorator face
- Steel mounting strap

Application

Hubbell-Pro Heavy Duty Hospital Grade

General

Color	Light Almond
Horsepower - Maximum	1
Indicator(s) Type	Green LED
Item Type	Style Line Decorator Duplex
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	<ul style="list-style-type: none">• Electrical - Current Interrupting - Certified for current interrupting at full rated current• Electrical - Dielectric Voltage - Withstands 2,000V minimum• Environmental - Flammability - UL 94V-2• Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact)• Mechanical - Product Identification - Ratings are a permanent part of the device• Mechanical - Terminal



Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 V
Wattage	2500 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none">• Certified to CSA, C22.2, No. 42 File 285• Fed. Spec. W-C-596• NEMA® WD-6 Compliant• UL Listed to UL498 File No. E2186
----------------------	--

Nema Rating	5-20R
-------------	-------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalog Page - Wiring A-22 Catalog page](#)
[Catalog Page - Wiring M9 Catalog page](#)
[Catalogs - Wiring Full Catalog](#)
[Literature - Tamper-Resistant Receptacles for Healthcare](#)
[Literature - WLBD026_Duct Products Brochure_WEB](#)
[Literature - Hubbell-PRO Hospital Grade TR Receptacles](#)
[Literature - Hubbell-Pro Hospital Grade Receptacles](#)
[Warranty - Industrial & Commercial Products](#)
[Video - Tamper-Resistant Receptacles](#)

Related Products

[2182I AI - Straight Blade Devices, Decorator Duplex](#)

	Accommodation - #12-#10 AWG stranded or solid copper wire only	Product Description - 20A 125V, 2-Pole 3-Wire Grounding, 5-20R Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R
	<ul style="list-style-type: none">Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA	P26LA - Wallplate, 1-Gang, 1) Decorator, Light Almond
Series	Hubbell-Pro	HBL8300LAMRI - Straight Blade Devices, Receptacles, Duplex, Hospital MRI Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Light Almond
Style	Style Line decorator	HBL8315CAT - Straight Blade Devices, Male Plug, Insulgrip, Hospital Grade, Angled, 2-Pole 3-Wire Grounding, 20A 125V, 5-20P, Clear, Single Pack
Type	Duplex Receptacle	2182WLTRA - Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 5-20R
UPC	783585541983	

Dimensions

Dimensions	3.28 in x 1.57 in x 1.15 in
Height	1.15 in
Length	3.28 in
Weight	0.2 lb
Width	1.57 in



A proud member of the Hubbell Family.