

Straight Blade Devices
15A, 125V, 2 Pole, 3 Wire Grounding
Miscellaneous Receptacles

HUBBELL

Ordering Information

Description Replacement receptacle for HBL5236	Device Color Brown	UPC 783585014562	Catalog Number HBL5236M2
---	-----------------------	---------------------	-----------------------------

Listings

UL Listed to UL498 File E2186
Certified to CSA, C22.2, No. 42 file 285
NEMA® WD-6 Compliant

Specifications

Face	Phenolic
Base	Phenolic
Power Contacts	.032" (.81) Brass

Performance

Electrical

Current Interrupting Certified for current interrupting at full rated current
Dielectric Voltage Withstands 2,000V minimum

Mechanical

Product Identification Ratings are a permanent part of the device
Terminal Accommodation #14-#10 AWG copper stranded or solid conductor only
Terminal Identification Terminals identified in accordance with UL 498 and CSA

Environmental

Flammability UL 94 V-2 or better
Operating Temperatures Maximum continuous 75°C; minimum -40°C (w/o impact)



Resources

[eCatalog](#)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

