

Hubbellok® Devices  
 Switched Safety Enclosures  
 Switched Enclosure  
 Features

- Accommodates 30-Amp, 4 Wire Hubbellock Receptacle
- Type 3R Rainproof or 12K Dust-tight
- Molded Valox Resists Abuse, Corrosion and Enhances Safety
- Lockable Handle Meets OSHA Lockout Requirements

**Ordering Information**

Description	Device Color	UPC	Catalog Number
Switched enclosure for use with 3 pole 4 wire 30A Hubbellock receptacle	Gray	783585006000	SEHBL3

**Listings**

Listed to UL Standard  
 CSA Certified Type 3R and 12K Enclosure Rating

**Specifications**

Base	PBT
Top	PBT
Handle	PBT
Conduit Hub	Zinc 3/4" watertight
Enclosure Gasket	Neoprene
Shaft	PBT

**Performance**

<b>600V RMS</b>	
Electrical	Operations
<b>Electrical</b>	
Current Interrupting	Certified for current interrupting at full rated current and voltage
Dielectric Voltage	Withstands 3,000V minimum
Environmental	Max. Working Voltage
<b>External fully adjustable</b>	
Mechanical	Product Identification
<b>Identification and ratings</b>	
Mechanical	Terminal Identification
<b>In accordance with UL</b>	
Mechanical	Mounting
<b>In accordance with UL,</b>	
Environmental	Flammability
<b>IP54 suitability</b>	
Environmental	Operating Temperature
<b>Maximum continuous</b>	
Environmental	UV Resistance
<b>Mechanical 10,000</b>	
Mechanical	Impact Resistance
<b>UL94 – 5 VA and V0</b>	
Environmental	Moisture Resistance

# HUBBELL



**Accessories**

All materials are UV stabilized      Receptacle Accommodation

**Resources**

eCatalog

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

