

Bottom Bracket Compatibility Matrix

Road

Commonly used by	Frame standard	Inner dia. mm	Shell width mm	Crank types					
				All Shimano compatible (24 mm)	SRAM GXP (24/22.2 mm)	Campagnolo Ultra Torque (25 mm)	Campagnolo Pro-Tech (25mm)	SRAM DUB Road (29 mm)	30 mm**
Specialized	BSA Thread	-	68						
Pinarello	ITA Thread	-	70						
Colnago	T45	-	82.5						
Ventum, Quintana Roo	T47-68	-	68						
Factor	T47A	-	77						
Trek	T47-86	-	86						
Giant, BMC, Scott, Canyon	BB86	41	86.5						
Ventum	PF30	46	68						
Cannondale	PF30a	46	73						
Cervélo	BBright	46	79						
Open, 3T, Orbea	EVO386	46	86.5						
Specialized, Cannondale	BB30	42	68						

MTB

Commonly used by	Frame standard	Inner dia. mm	Shell width mm	Crank types			
				All Shimano compatible (24 mm)	SRAM GXP (24/22.2 mm)	SRAM DUB (29 mm)	BB30 (30mm)
Specialized	BSA Thread	-	73				
Trek, Giant, BMC, Scott, Canyon	BB92 (BB86/89)	41	89.5/91.5				
Cannondale	BB30	42	73/83				
Cannondale, Niner	PF30	46	73				
	T47 - 73	-	73				

- All road bottom brackets are standard with a 4-year warranty. Choose a coated version for even lower friction and lifetime warranty
- Gravel bottom brackets use Road compatibility and built with long life grease and are coated only with lifetime warranty
- All MTB bottom brackets are coated only with lifetime warranty
- Special BB65 LOOK bearings available
- BB90 Bearings for Shimano and GXP available
- Most products are available in both black and red
- See installation and maintenance videos on ceramicspeed.com → Support or scan this QR code for direct access
- For best performance and longevity, always service with one of the three CeramicSpeed UFO Grease options:



All-Round Grease



Long-Life Grease



Race Day Grease

* Bearings only, installation will require Campagnolo Press Fit cups.
 ** 30 mm cranks with a short spindle may have limited compatibility.
 *** Does not fit a FSA crank from 2016 or newer.
 **** Only BB30 fits shell width of 83 mm.