

Sep. 1. 2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD														
RATING	OPERATING TEMPERATURE RANGE	-35°C TO 85°C (NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO 60°C										
	VOLTAGE	250V AC	APPLICABLE CONNECTOR	MDF7-*P-2. 54DSA (**)										
	CURRENT	3A												
SPECIFICATIONS														
ITEM	TEST METHOD	REQUIREMENTS	QT	AT										
CONSTRUCTION														
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X										
MARKING	CONFIRMED VISUALLY.		X	X										
ELECTRIC CHARACTERISTICS														
CONTACT RESISTANCE	100mA (DC OR 1000 Hz).	30mΩ MAX.	X	—										
INSULATION RESISTANCE	500V DC.	1000MΩ MIN.	X	—										
VOLTAGE PROOF	650V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—										
MECHANICAL CHARACTERISTICS														
CONTACT INSERTION AND EXTRACTION FORCES	□0.635±0.002 mm BY STEEL GAUGE.	INSERTION FORCE: 4.4 N MAX. EXTRACTION FORCE: 0.4 N MIN.	X	—										
MECHANICAL OPERATION	50TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 30mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—										
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—										
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—										
ENVIRONMENTAL CHARACTERISTICS														
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ 5 TO 35→85→5 TO 35°C TIME 30→10 TO 15→30→10TO15min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—										
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—										
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48h.	① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X	—										
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JEITA-39)	① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X	—										
RESISTANCE TO SOLDERING HEAT	【FLOW CONDITION BY AUTOMATIC SOLDERING UNIT】 SOLDER TEMPERATURE 260±5°C, FOR IMMERSION DURATION 10s.(ONE TIME) 【RECOMMENDED MANUAL SOLDELING CONDITION】 SOLDERING IRON TEMPERATURE 350°C SOLDERING TIME : WITHIN 3 SECONDS. DO NOT APPLY ANY FORCE TO THE CONTACTS.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	—										
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE 245±5°C FOR IMMERSION DURATION 5s.	SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMERSED.	X	—										
<table border="1"> <thead> <tr> <th>COUNT</th> <th>DESCRIPTION OF REVISIONS</th> <th>DESIGNED</th> <th>CHECKED</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td> 6</td> <td>DIS-H-006198</td> <td>YN. SAKAMOTO</td> <td>TS. MIYAZAKI</td> <td>11. 10. 12</td> </tr> </tbody> </table>					COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	6	DIS-H-006198	YN. SAKAMOTO	TS. MIYAZAKI	11. 10. 12
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE										
6	DIS-H-006198	YN. SAKAMOTO	TS. MIYAZAKI	11. 10. 12										
REMARKS NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT.			APPROVED	KJ. KATAYOSE 05. 01. 05										
			CHECKED	KI. AKIYAMA 05. 01. 05										
UNLESS OTHERWISE SPECIFIED , REFER TO JIS C 5402 .			DESIGNED	TH. ARAI 05. 01. 05										
			DRAWN	TH. ARAI 05. 01. 05										
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-162738-11											
	SPECIFICATION SHEET		PART NO.	MDF7-*S-2. 54DSA (56)										
	HIROSE ELECTRIC CO., LTD.		CODE NO.	1/1										