

BOARD MOUNT



Ultra-Compact SIP | 1 ~ 15 W

- Wide input voltage range options (305 Vac)
- 3.3 ~ 24 Vdc outputs
- Vertical and right-angle SIP
- Flexible design for a wide array of applications



Encapsulated | 2 ~ 60 W

- Universal (264 Vac) and wide (305 Vac) input voltage range options
- 3.3 ~ 48 Vdc outputs
- Class B emissions



Open Frame | 6 ~ 60 W

- Universal (264 Vac) and wide (305 Vac) input voltage range options
- 3.3 ~ 48 Vdc outputs
- No load power consumption as low as < 0.075 W

CHASSIS MOUNT



Encapsulated | 3 ~ 60 W

- Universal (264 Vac) and wide (305 Vac) input voltage range options
- 3.3 ~ 48 Vdc outputs
- Class B emissions



Open Frame | 12 ~ 550 W

- Universal input voltage range options (264 Vac)
- 3.3 ~ 58 Vdc outputs
- Industry standard footprints (2" x 3", 2" x 4", 3" x 5")



Metal Case | 15 ~ 500 W

- Universal (264 Vac) and wide (305 Vac) input voltage range options
- 3.3 ~ 56 Vdc outputs
- Conformal coating & terminal cover options

CHASSIS MOUNT



U-Frame | 120 ~ 400 W

- Universal input voltage range options (264 Vac)
- 3.3 ~ 54 Vdc outputs
- Single, dual, & triple output versions available
- Optional fan



+ Medical | 40 ~ 550 W

- Universal input voltage range options (264 Vac)
- 3.3 ~ 58 Vdc outputs
- Industry standard footprints (2" x 3", 2" x 4", 3" x 5")
- Metal case and open frame packages
- 2 x MOPP

DIN RAIL



DIN Rail | 3 ~ 300 W

- Universal (264 Vac) and wide (305 Vac) input voltage range options
- 3.3 ~ 48 Vdc outputs
- Slim design with easy electrical connections
- Standard DIN-Rail compatible clips

EXTERNAL



Wall Plug | 3 ~ 45 W

- Universal input voltage range options (264 Vac)
- 3.3 ~ 48 Vdc outputs
- North America, EU versions
- + Medical versions available



Desktop | 12 ~ 250 W

- Universal input voltage range options (264 Vac)
- 5 ~ 56 Vdc outputs
- GaN technology models available
- + Medical versions available



Multi-Blade | 5 ~ 36 W

- Universal input voltage range options (264 Vac)
- 5 ~ 48 Vdc outputs
- 5 optional blades for global use
- + Medical versions available

ISOLATED BOARD MOUNT



Low Power | 0.75 ~ 4 W

- DIP, SIP, & SMT packages
- 2.97 ~ 75 Vdc inputs
- -24 ~ 24 Vdc outputs
- 1000 ~ 6000 Vdc isolation
- Regulated & unregulated models



Mid Power | 5 ~ 49 W

- DIP, SIP, & SMT packages
- 9 ~ 1500 Vdc inputs
- -24 ~ 24 Vdc outputs
- 1500 ~ 5600 Vdc isolation
- 1" x 1", 2" x 1", 2" x 2" footprints



High Power | 50 ~ 600 W

- DIP packages
- 9 ~ 160 Vdc inputs
- 3.3 ~ 48 Vdc outputs
- 1500 ~ 2250 Vdc isolation
- 1/2, 1/4, & full brick models



1" X 1" Footprint | 6 ~ 30 W

- 9 ~ 160 Vdc inputs
- 3.3 ~ 24 Vdc outputs
- Input voltage ratios up to 4:1
- 1500 ~ 2250 Vdc isolation
- Industry standard footprints



Ultra-Wide Input | 5 ~ 40 W

- 100 ~ 1500 Vdc inputs
- 5 ~ 24 Vdc outputs
- Input voltage ratios up to 10:1
- 4000 ~ 6000 Vdc isolation
- Ideal for renewable energy applications



Asymmetrical Converters | 3 ~ 30 W

- 18 ~ 75 Vdc inputs
- 5 ~ 24 Vdc outputs
- Input voltage ratios up to 4:1
- 1500 ~ 3000 Vdc isolation
- Independently isolated outputs

ISOLATED CHASSIS & DIN RAIL



Low to Mid Power | 5 ~ 49 W

- 9 ~ 1200 Vdc inputs
- -24 ~ 24 Vdc outputs
- Compact DIN rail and chassis mount packages



High Power | 50 ~ 600 W

- 9 ~ 75 Vdc inputs
- 3.3 ~ 48 Vdc outputs
- Rugged aluminum package & integrated heat sink



Ultra-Wide Input | 5 ~ 40 W

- 100 ~ 1200 Vdc inputs
- 5 ~ 24 Vdc outputs
- Input voltage ratios up to 10:1

NON-ISOLATED BOARD MOUNT



Open Frame Switching Regulators

- 0.5 & 1 A / 3-pin SIP packages
- 4.75 ~ 36 Vdc inputs
- 3.3 ~ 15 Vdc outputs
- Drop-in replacement to LM78 and LM79 linear regs



Enclosed Switching Regulators

- 0.5 & 1 A / 3-pin SIP, SMT packages
- 4.5 ~ 72 Vdc input range
- 1.5 ~ 24 Vdc outputs
- Drop-in replacement to LM78 and LM79 linear regs



Wire Leads

- 0.5 A
- 4.75 ~ 36 Vdc input range
- 3.3 ~ 15 Vdc outputs
- Flexible termination ideal for prototyping