

DATA SHEET

4XEM 25W USB-C Charger and 6FT USB-C/USB-C Cable Kit for Smartphones and USB-C Compatible Devices - Black

4XEM Part- 4X25WCHARGEKIT6B



For your convenience, 4XEM has put together this all-in-one USB-C charging kit. Designed to provide efficient and safe charging, this kit ensures that your devices, including the new iPhone 15, 15 Plus, 15 Pro and 15 Pro Max, stay powered up whenever you need them. With a sleek and compact design, the 4XEM 25W USB-C PD Charger is perfect for home, office, or travel use. Its USB Type-C charging port offers a universal solution, making it compatible with a wide range of devices. The kit also includes a high-quality 6ft/2m USB-C to USB-C cable, allowing for easy and seamless connectivity between your devices and the charger. The USB 3.2 Gen 2 cable supports a data transfer rate of 10Gbps, ensuring quick and efficient file transfers.

With a total power budget of 25W and Power Delivery technology, the 4XEM USB-C Charging Kit provides optimized charging for your devices. The power delivery pairs perfectly with the cable which is E-marked for 100W power delivery.

Order the 4XEM 25W USB-C Charging Kit today and enjoy fast, efficient, and safe charging for your devices. Stay powered up and connected wherever you go!

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

Features

USB-C 25W Fast Charging, Quick Charge 3.0 Wall Charger Features:

- 4XEM 25W PD USB-C Charger:
- 1x USB Type-C Female charging port
- 25W total power budget
- 25W Max Power Delivery
- CE certified
- Standard NA wall charger with non-retractable prongs
- Color: Black

4XEM 6FT/2M USB-C TO USB-C CABLE M/M USB 3.1 GEN 2 10GBPS:


- 10 Gbps data transfer rates
- E-marked for 100W power delivery
- Meets USB 3.2 Gen 2 industry standards
- USB-C to USB-C male connectors
- Bidirectional use (no designated input or output end)
- Supports video (source and display must support DP Alt Mode)
- 6FT in length
- Color: Black



Reversible USB Type C Connectors

Application

- Phone Calls
- At Home
- At the Office
- Travel



4XEM Products Are Available At Your Favorite Online Retailers

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

Warranty Information Warranty 1 year

Connector(s) Charging Port USB Type-C

Power Source Non-Polarized NEMA 1-15P (Standard NA Wall Outlet)

Fixed with Non-Retractable Prongs

Charging Cable Connector A USB Type-C Male Charging Cable Connector B USB Type-C Male

Operating Mode Passive
Direction Bidirectional

Performance Industry Standards (Cable) USB 3.2 Gen 2

Charging Protocols (Charger) FCP (5V, 9V, 12V) AFC (5V, 9V)

QC3+ (5V, 9V, 3.6-9V)

USB-PD 3.0 (25W, PPS, QC4+)

Apple 2.4A

Cable Data Transfer Rate 10Gbps

E-Marker 20V, 5A (100W)
Certifications CE (Charger)

Physical Characteristics Charger Color Black

Display No
LED Indicator(s) None

 Charger Height
 1.03 in [26.2 mm]

 Charger Width
 1.65 in [42.0 mm]

 Charger Length
 2.00 in [50.7 mm]

2.65 in [67.2 mm] (with power prongs)

Charger Weight 2.33 oz [40 g]

Charging Cable Longth Black

Charging Cable Length 5.91 ft [1.80 m]
Charging Cable OD 0.18 in [4.50 mm]
Charging Cable Weight 2.26 oz [64 g]

Power Total Power Budget 25W
Power Delivery 25W Max

Input Voltage 100-240VAC, 50Hz-60Hz @ 0.7A

Output Voltage (PD) 25W: 5V 3A, 9V 2.77A

25W PPS: 3.3V-5.9V 3A, 3.3V-11V 2.25A

Environmental Operating Temperature 0 to 40°C (32 to 104°F) Storage Temperature -20 to 80°C (-4 to 176°F

Storage Temperature -20 to 80°C (-4 to 176°F) Humidity 5% to 90% (non-condensing)

Packaging Information Package Type Poly-bag

Package Height 7.09 in [180 mm]
Package Width 4.72 in [120 mm]
Package Length 0.54 in [13.7 mm]
Shipping (Package) Weight 3.84 oz [109 g]

What's in the Box Included in Package 1x 25W USB-C PD Charger

1x 5.9ft/1.8m USB-C/USB-C Cable

Notes Notes Cable does support video, however, connected video source equipment and display must both support

Source equipment and display must both support DisplayPort Alt-Mode for functional A/V transmission.



^{*} Product appearance and specifications are subject to change without notice.

^{*} Same day shipping is only available for orders shipping within the United States.