

### **DATA SHEET**

4XEM's 45W GAN Charger USB-C + USB-A

#### Part- 4XGAN00645WW



Introducing the White 45W GAN Charger with 1 USB-C Port and 1 USB-A Port - the ultimate power solution for all your devices including the new iPhone 15, and 15 Plus as well as the advanced iPhone 15 Pro and Pro Max. This sleek and compact charger is designed to deliver fast and efficient charging for your USB-C and USB-A devices, with Power Delivery technology that guarantees optimal charging speed and efficiency.

The charger features one USB-C port and one USB-A port, allowing you to charge multiple devices simultaneously. The USB-C port is equipped with Power Delivery technology, which means you can charge your USB-C devices with up to 45W of power, providing optimal charging speed and efficiency. The USB-A port is also capable of fast charging your USB-A devices.

The white color design and compact size make it easy to take with you on the go, and it's perfect for traveling, working remotely, or just keeping in your bag for everyday use.

# WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





#### **DATA SHEET**

## **Features**

- 45W total power output for fast and efficient charging of multiple devices
- 1 USB-C port and 1 USB-A port, providing flexibility to charge a variety of devices.
- USB-C port feature Power Delivery technology for lightning-fast charging of devices that support it.
- Sleek white design with an integrated LED indicator for easy monitoring of charging status
- Compact and portable design makes it easy to take with you on-the-go.
- Overcurrent, overvoltage, and short circuit protection for added safety and peace of mind.



### Application

- Charging
- At Home
- At the Office
- Travel



Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





### **DATA SHEET**

Warranty Information	Warranty	1 Year
Connector(s)	Charging Port(s)	1x USB Type-C Female 1x USB Type-A Female Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Non-Retractable Prongs
	Power Source	
Performance	Industry Standards Certifications	USB-PD 3.0 CE
Physical Characteristics	Colour Display LED Indicator(s) Power Cable Length Product Height Product Width Product Length Weight of Product	White No Power: Aqua N/A 2.05 in [52.0 mm] 1.17 in [29.9 mm] 2.05 in [52.0 mm] (Body Only) 2.67 in [67.9 mm] (Incl. power prongs) 3.53 oz [100 g]
Power	Total Power Budget Power Delivery Input Voltage Output Voltage (C1) Output Voltage (A1) Output Voltage (C1) + (A1)	45W 45W Max 100-240VAC, 50Hz-60Hz @ 1A 45W: 5/9/12/15V 3A, 20V 2.25A 18W: 5V 3A, 9V 2A, 12V 1.5A 45W MAX - 27W: 5V 2.4A, 9V 3A, 12V 2.25A, 15V 1.8A, 20V 1.35A + 18W: 5V 2.4A, 9V 2A, 12V 1.5A
Environmental	Operating Temperature Storage Temperature Humidity	32°F to 104°F [0ºC to 40ºC] -4°F to 176°F [-20°C to 80°C] 5% to 90% (non-condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Poly-Bag 6.00 in [152.4 mm] 4.00 in [101.6 mm] 1.18 in [30.1 mm] 3.60 oz [102 g]
What's in the Box	Included in Package	1x 45W USB-C + USB-A GaN Charger

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com