



4XEM's 45W Wall Charger Dual USB-

C 4XEM Part- 4XGAN00845WW



4XEM's 45W USB-C offers amazing charging power and speed with two USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming the new standard for charging devices the new iPhone 15, and 15 Plus as well as the advanced iPhone 15 Pro and Pro Max, allowing for up to 45W charging for power at faster speeds. This device features 2x USB-C ports. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C Wall Charger.

Problem it solves: Charge one to two USB devices with reliable power and speed using 4XEM's 45W GaN Charger.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com







Features:

- 45-Watt power budget
- 2x USB-C port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging

Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging





4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

1 Year Warranty Information Warranty

2x USB Type-C Female Connector(s) Charging Port(s)

Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Power Source

Fixed with Non-Retractable Prongs

Performance **Industry Standards** USB-PD 3.0 CE

Certifications

White Physical Characteristics Colour

No Display

Power: Blue LED Indicator(s)

N/A Power Cable Length

1.26 in [32.00 mm] Product Height 1.37 in [34.7 mm] Product Width

2.39 in [60.8 mm] (Body Only) Product Length

3.02 in [76.6 mm] (Incl. power prongs)

3.25 oz [92 g] Weight of Product

45W Power Total Power Budget

45W Max Power Delivery

100-240VAC, 50Hz-60Hz @ 1A Input Voltage 45W: 5/9/12/15V 3A, 20V 2.25A Output Voltage (C1/C2)

45W MAX - 27W: 5V 2.4A, 9V 3A, 12V 2.25A, Output Voltage (C1) + (C2) 15V 1.8A, 20V 1.35A + 18W: 5V 2.4A, 9V 2A,

12V 1.5A

32°F to 104°F [0°C to 40°C] Environmental Operating Temperature

Storage Temperature

Humidity

-4°F to 176°F [-20°C to 80°C] 5% to 90% (non-condensing)

Packaging Information Poly-Bag Package Type

4.00 in [101.6 mm] Package Height 3.00 in [76.2 mm] Package Width 1.37 in [34.9 mm] Package Length

Shipping (Package) Weight 3.32 oz [94 g]

What's in the Box 1x 45W Dual USB-C GaN Charger Included in Package

Notes Notes

Product appearance and specifications are subject to change without notice.
Same day shipping is only available for orders shipping within the United States

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com

