

DATA SHEET

4XEM's 65W Wall Charger Dual USB-C

4XEM Part- 4XGAN00865WB



4XEM's 65W USB-C offers amazing charging power and speed with two USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming the new standard for charging devices, allowing for up to 65W charging for power at faster speeds. This device features 2x USB-C ports. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C Wall Charger.

Problem it solves: Charge one to two USB devices with reliable power and speed using 4XEM's 65W Charger.

4XEM Products Are Available At Your Favorite Online Retailers

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com







DATA SHEET

Features:

- 65-Watt power budget
- 2x USB-C port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging

Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging



4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

Warranty Information	Warranty	1 Year
Connector(s)	Charging Port(s) Power Source	2x USB Type-C Female Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Non-Retractable Prongs
Performance	Industry Standards Certifications	USB-PD 3.0 CE
Physical Characteristics	Colour Display LED Indicator(s) Power Cable Length Product Height Product Width Product Length Weight of Product	Black No Power: Blue N/A 1.26 in [32.00 mm] 1.37 in [34.7 mm] 2.39 in [60.8 mm] (Body Only) 3.02 in [76.6 mm] (Incl. power prongs) 3.39 oz [96 g]
Power	Total Power Budget Power Delivery Input Voltage Output Voltage (C1/C2) Output Voltage (C1) + (C2)	65W 65W Max 100-240VAC, 50Hz-60Hz @ 1.5A 65W: 5/9/12/15V 3A, 20V 3.25A 65W MAX - 45W: 5/9/12/15V 3A, 20V 2.25A + 20W: 5V 23A, 9V 2.22A, 12V 1.67A
Environmental	Operating Temperature Storage Temperature Humidity	32°F to 104°F [0ºC to 40ºC] -4°F to 176°F [-20°C to 80°C] 5% to 90% (non-condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Poly-Bag 4.00 in [101.6 mm] 3.00 in [76.2 mm] 1.37 in [34.9 mm] 3.46 oz [98 g]
What's in the Box	Included in Package	1x 65W Dual USB-C GaN Charger
Notes	Notes	

* Product appearance and specifications are subject to change without notice.

* Weights and measurements are approximate.

Product appearance and specifications are subject to change without notice.
Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com