

**DATA SHEET** 

4XEM 25W USB-C 6FT Charging Kit compatible for iPhone 15 Pro and iPhone 15 Pro Max

4XEM Part- 4XIPHNPROKIT6



For your convenience, 4XEM has put together this all-in-one USB-C charging kit. Designed to provide efficient and safe charging, this kit ensures that your iPhone 15 Pro and Pro Max devices stay powered up whenever you need them. With a sleek and compact design, the 4XEM 25W USB-C PD Charger is perfect for home, office, or travel use. Its USB Type-C charging port offers a universal solution that utilizes the advancements made in the iPhone 15 Pro and Pro Max. The kit also includes a high-quality 6ft/2m USB-C to USB-C cable, allowing for easy and seamless connectivity between your devices and the charger. The USB 3.2 Gen 2 cable is supported by the optimized iPhone 15 and offers a data transfer rate of 10Gbps, ensuring quick and efficient file transfers. With a total power budget of 25W and Power Delivery technology, the 4XEM USB-C Charging Kit provides optimized charging for your devices. The power delivery pairs perfectly with the cable which is E-marked for 100W power delivery.

Order the 4XEM 25W USB-C Charging Kit today and enjoy fast, efficient, safe and improved mobile experience for your iPhone 15 Pro devices. Stay powered up and connected wherever you go!

**4XEM Products Are Available At Your Favorite Online Retailers** 

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

# **Features**

### USB-C 25W Fast Charging, Quick Charge 3.0 Wall Charger Features:

- 4XEM 25W PD USB-C Charger:
- 1x USB Type-C Female charging port
- 25W total power budget
- 25W Max Power Delivery
- CE certified
- Standard NA wall charger with non-retractable prongs
- Color: White

#### 4XEM 6FT/2M USB-C TO USB-C CABLE M/M USB 3.1 GEN 2 10GBPS White:


- 10 Gbps data transfer rates
- E-marked for 100W power delivery
- Meets USB 3.2 Gen 2 industry standards
- USB-C to USB-C male connectors
- Bidirectional use (no designated input or output end)
- Supports video (source and display must support DP Alt Mode)
- 6FT in length
- Color: White



# Reversible USB Type C Connectors

# **Application**

- Phone Calls
- At Home
- · At the Office
- Travel



**4XEM Products Are Available At Your Favorite Online Retailers** 

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





## **DATA SHEET**

Warranty Information Warranty 1 year

**Charging Port** USB Type-C Connector(s)

Power Source Non-Polarized NEMA 1-15P (Standard NA Wall Outlet)

Fixed with Non-Retractable Prongs

Charging Cable Connector A **USB Type-C Male** Charging Cable Connector B USB Type-C Male

Operating Mode **Passive** Direction Bidirectional

Performance Industry Standards (Cable) USB 3.2 Gen 2 Charging Protocols (Charger) FCP (5V, 9V, 12V)

AFC (5V, 9V)

QC3+ (5V, 9V, 3.6-9V)

USB-PD 3.0 (25W, PPS, QC4+)

Apple 2.4A 10Gbps

Cable Data Transfer Rate

20V, 5A (100W) E-Marker Certifications CE (Charger)

**Physical Characteristics** Charger Color White

Display Nο LED Indicator(s) None Charger Height

1.03 in [26.2 mm] Charger Width 1.65 in [42.0 mm] Charger Length 2.00 in [50.7 mm]

2.65 in [67.2 mm] (with power prongs)

Charger Weight 2.33 oz [40 g] Charging Cable Color White

Charging Cable Length 5.91 ft [1.80 m] Charging Cable OD 0.18 in [4.50 mm] Charging Cable Weight 2.26 oz [64 g]

Power Total Power Budget 25W Power Delivery 25W Max

> Input Voltage 100-240VAC, 50Hz-60Hz @ 0.7A

Output Voltage (PD) 25W: 5V 3A, 9V 2.77A

25W PPS: 3.3V-5.9V 3A, 3.3V-11V 2.25A

Environmental Operating Temperature 0 to 40°C (32 to 104°F)

Storage Temperature -20 to 80°C (-4 to 176°F) Humidity 5% to 90% (non-condensing)

Packaging Information Package Type Poly-bag

Package Height 7.09 in [180 mm] Package Width 4.72 in [120 mm] Package Length 0.54 in [13.7 mm] Shipping (Package) Weight 3.84 oz [109 g]

What's in the Box 1x 25W USB-C PD Charger

Included in Package

1x 5.9ft/1.8m USB-C/USB-C Cable

Notes Notes Cable does support video, however, connected video

source equipment and display must both support DisplayPort Alt-Mode for functional A/V transmission.



<sup>\*</sup> Product appearance and specifications are subject to change without notice.

<sup>\*</sup> Same day shipping is only available for orders shipping within the United States.