

DATA SHEET

4XEM's 3-Port DP to HDMI Multi-Monitor Hub

4XEM Part- 4XMST04



4XEM's 3-port DP to DP and HDMI multi-monitor hub is a premier video device. This device offers the ability to increase your productivity by utilizing up to 3 separate screens in conjunction with your main device. Connect, up to, two DisplayPort monitors and a single HDMI to your device to expand your work or play station to new heights. Supporting the ability to mirror and extend displays you also can adjust the displays as you see find. Such display applications can include spanning spreadsheets over monitors, panoramic viewing, and editing audio and video clips to name a few. Spread out your displays and working capabilities with 4XEM's multimonitor hubs.


Problem it solves: Connect three devices to your DisplayPort display easily with one convenient device.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com







Features

- 2 DisplayPort port
- 1 HDMI port
- DisplayPort male connector
- Supports Extended and Duplicate screen modes
- Supports 8K uncompressed video (7680x4320 @ 30Hz)
- Supports 4K ultra-HD video (3840x2160 @ 120Hz)
- Supports Ultra-wide displays
- Lightweight and portable design



Application

- Home theatre
- Office
- Business Presentations
- Multi-screen display

4XEM Products Are Available At Your Favorite Online Retailers

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

Warranty Information Warranty 1 Year

Hardware Chipset ID Realtek RTD2183 Torex XC6220B331

> Max Uncompressed Bandwidth HBR3 - 32.4Gbps/25.92Gbps

Industry Standards DisplayPort 1.4

> **HDMI 2.0 DSC 1.2** HDCP 1.4/2.3

Connector(s) Connector A (Source) DisplayPort - Male

Connector B (Display) DisplayPort (x2) - Female

HDMI - Female

Other Micro-USB - Female (Power Only)

Performance **Audio Specifications** Up to 32 Channels

Maximum Digital Resolutions 7680x4320 (8K), 30Hz, 8bpc (Uncompressed) 3840x2160 (4K), 120Hz, 8bpc (Uncompressed)

(for single display)

OS Compatibility Windows 10 Software

Power Source Power USB

Input Voltage 5V DC @ 2A **Power Consumption** 10W

Physical Characteristics Colour Grey

Shell Material Aluminium Power Cable Length 23.03 in [585 mm] Attached Cable Length 6.1 in [155 mm] Product Height 0.57 in [14.5 mm] Product Width 3.31 in [84.2 mm] 2.02 in [51.2 mm] Product Length (Body) 10.20 in [259 mm] Product Length (Overall) 3.25 oz [92 g]

Packaging Information Package Type Poly-bag

Weight of Product

Package Height 7.76 in [197 mm] Package Width 5.83 in [148 mm] Package Length 0.64 in [16.2 mm]

Shipping (Package) Weight 4.09 oz [116 g]

1x 3-port DisplayPort/HDMI MST Hub What's in the Box Included in Package

1x Micro-USB Power Cable

Notes System Requirements "DisplayPort 1.2 with MST+HBR2 support from the Notes

GPU is required for independent display output. DisplayPort 1.4 support from GPU required for increased bandwidth and use of DSC.

"Combined bandwith of all output streams cannot exceed that of the available input bandwidth.

External power supply required for proper operation."

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com

