



4XEM's 38W USB-C and USB-A Charger

4XEM Part- 4XPOWERAC



4XEM's 38W USB-C and A Charger offers two USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for 18Ws of charging to power to legacy and current devices. USB-C is rapidly becoming a new standard for charging devices, allowing for 20W charging power at faster speeds. Keep multiple USB devices charged on the go or at home reliably with 4XEM's USB-C and A Charger.

Problem it solves: Charge one or two USB devices with reliable power and speed with 4XEM's 38W USB-C and USB-A Charger.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com







Features

- 38-Watt power
- 1x 18W USB-A port
- 1x 20W USB-C port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size



Application

- Home
- Office
- Travel
- Meetings

4XEM Products Are Available At Your Favorite Online Retailers

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com



DATA SHEET

1 year Warranty Information Warranty

Connector(s) 1x USB Type-C Charging Port(s) 1x USB Type-A

> Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Power Source

> > **Direct Attached**

USB-PD 3.0 Performance **Industry Standards**

Qualcomm QC 3.0

AFC FCP

White **Physical Characteristics** Colour

No Display No LED Indincacator

1.20 in [30.6 mm] Product Height 1.69 in [42.8 mm] **Product Width** 1.69 in [42.9 mm] Product Length

2.32 in [58.9 mm] (with power prongs)

1.62 oz [46 g] Weight of Product

20W Power Total Power Budget

20W Power Delivery

100-240VAC 0.5A, 50Hz-60Hz Input Voltage/Current

USB-C: 5V 3A, 9V 2.22A, 12V 1.67A (20W MAX) Output Voltage/Current USB-A: 5V 3A, 9V 2A, 12V 1.5A (18W MAX) USB-C+USB-A: 5V 3.1A (15.5W - Shared)

Environmental Operating Temperature

Storage Temperature Operating Elevation

14°F to 104°F [-10°C to 40°C] @ 10%-90% RH (non-condensing) -4°F to 185°F [-20°C to 85°C] @ 5%-95% RH (non-condensing)

-65m-2000m Above Sea Level

Packaging Information Package Height

Package Width Package Length 3.00 in [76.2 mm] 1.25 in [31.8 mm]

4.00 in [101.6 mm]

Shipping (Package) Weight

1.69 oz [48 g]

1x 2-Port USB Charger What's in the Box Included in Package

Product appearance and specifications are subject to change without notice. * Product appearance and specifications are subject to change without notice.

* Weights and measurements are approximate. Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep tschaus@4xem.com 1-866-999-4936 Ext.104

