

4XEM Clear USB 3.0 to SATA Hard Drive Enclosure

4XEM Part- 4XST239



With a durable and easily portable design 4XEM's Clear USB 3.0 SATA Hard Drive enclosure is a product that offers protection and mobility. Compatible with both SATA HDD and SSD as well as multiple host devices this device can fit into a variety of situations. With USB 3.0 the enclosure can offer data transfer rates of up to 5Gbps, 10 times faster than 2.0. This enclosure provided a secure way to recover your images and files from "dead" devices. Keep your data safe and close by with this Clear Hard Drive Enclosure.

Problem it solves: Recover your images and other important files from your dead devices without the fear of damage, with this mobile and sturdy enclosure.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features:

- Detachable Micro USB to USB Type-A connector cable
- SATA III Operating Mode
- Compatible for 2.5" SATA drive types
- Easy swap/ plug and play, no drivers needed
- LED Power Indicators
- Backwards compatible with USB 2.0/1.1
- Compatible with Windows XP or later, Mac OS X and Linux
- Supports Transfer Rates up to 5Gbps
- Supports standard 2.5" 7mm/9mm SATA I/II/III Hard Drives and SSD up to 2TB
- Supports UASP transfer protocol, 20% faster than regular USB 3.0 interface



Application

- Home Office
- Office
- Mobile
- Storage expansion

4XEM Products Are Available At Your Favorite Online Retailers





DATA SHEET

Warranty Information	Warranty	1 Year	
Features/Hardware	Compatible Drive Types	2.5" SATA	
	Number of Drives	1	
	Drive Installation	Fixed	
	Fan(s)	No	
	Heatsink	No	
Connector(s) & Performance	Chipset ID	JMicron - JMS578	
	Operating Mode	USB 3.1 Gen 1	
	Host Data Line Speed	5 Gbps	
	Host Connectors	Micro-USB SuperSpeed Type-B	
	Drive Connectors	SATA	
Software	Drive Operating Mode	SATA III	
	Maximum Data Transfer Rate*	625 MB/s	
	OS Compatibility	Windows XP or later (32-bit & 64-bit) Mac OSX Linux	
	Physical Characteristics	Color	Copper (Transparent)
		Shell Material	Plastic
LED Indicators		Power/Activity: Blue	
Cable Type		Detachable	
Cable Length		17.52 in [445 mm]	
Max Drive Height		0.37 in [9.5 mm]	
Product Height		0.53 in [13.5 mm]	
Product Width		3.11 in [78.9 mm]	
Product Length		4.93 in [125.1 mm]	
Weight of Product (Empty)		1.90 oz [54 g]	
Weight of Product (Occupied)	5.22 oz [148 g]*		
Power	Power Source	Bus Powered	
	Power Consumption	4.5W	
Environmental	Operating Temperature	32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condensing)	
	Storage Temperature	14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condensing)	
Packaging Information	Package Type	Box	
	Package Height	5.26 in [133.7 mm]	
	Package Width	3.24 in [82.4 mm]	
	Package Length	1.25 in [31.7 mm]	
	Shipping (Package) Weight	3.46 oz [98 g]	
Special Notes / Requirements	Notes	"625 MB/s is the theoretical maximum bandwidth available. Data throughput will be less due to overhead. Actual performance will also vary due to factors such as host processor, SSD/HDD used, drive buffer/controller, and other devices sharing the same bus, etc. Real world performance is typically 450 MB/s sequential read and 450 MB/s sequential write using an SSD; 85 MB/s sequential read 85 MB/s sequential write for a 5400RPM HDD. Occupied weight measured with Seagate Momentus Thin 500GB HDD."	

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

