

4XEM's USB 3.0 Full HD Travel Mini Dock

4XEM Part- 4XUG39DH2



Travel in style and stay connected with our Full HD Travel Mini Dock. This compact and lightweight device packs a punch with 2 USB 3.0 ports, HDMI port, VGA port, Gigabit Ethernet adapter, and an SD card reader. Perfect for on-the-go professionals and travelers, this mini dock allows you to connect to multiple devices and peripherals, ensuring seamless productivity and entertainment. Optimize your workflow and elevate your travel experience with our Full HD Travel Mini Dock - the ultimate in portability and connectivity.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features

- Full HD capability: Experience high-definition visuals and audio on the go.
- Compact and portable design: Easily fit the mini dock in your bag or pocket for seamless connectivity on the go.
- 2 USB 3.0 ports: Connect and power multiple devices such as external hard drives, cameras, and more.
- HDMI port: Connect to external monitors or TVs for an enhanced viewing experience.
- VGA port: Connect to older monitors or projectors for added versatility.
- Gigabit Ethernet adapter: Enjoy fast and stable wired internet connection.
- SD card reader: Quickly transfer and access files from your camera or other SD-enabled devices.
- Seamless productivity and entertainment: Connect to multiple devices and peripherals to optimize your workflow and elevate your travel experience.



## Application

- Home theatre
- Small business
- Travel
- Business Presentations

**4XEM Products Are Available At Your Favorite Online Retailers**



|                              |   |  |
|------------------------------|---|--|
| Warranty Information         | Warranty  | 2 Years  |
| Features/Hardware            | 4K Support<br>Displays Supported<br>USB Ports<br>Fast-Charge Port(s)<br>Network<br>SD Card Reader<br>Audio<br>Power Delivery<br>Lock Slot<br>Industry Standards<br><br>Chipset ID   | No<br>2<br>2<br>No<br>Yes<br>Yes<br>No<br>No<br>No<br>No<br>HDMI 1.3<br>HDCP 1.4<br>Secure Digital (SD v2.0)<br>DisplayLink - DL3900<br>VIA - VL813<br>Genesys Logic - GL3224  |
| Connector(s)                 | Host Bus Type<br>Host Connector<br>Host Connector Cable<br>Connector Type(s)/Rate(s)  | USB 3.0 (5Gbps)<br>USB Type-A<br>Fixed Attached<br>1x HDMI 1.3 (10.2Gbps)<br>1x VGA<br>2x USB 3.0 Type-A (5Gbps)<br>1x RJ-45 (10/100/1000Mbps)<br>1x SDHC (25 MB/s)<br>1x MicroSDHC (25 MB/s)<br>1x MicroUSB Type-B (Power Input Only) |
| Performance                  | Maximum Digital Resolutions<br><br>Maximum Analog Resolutions<br>Audio Specifications   | Single Monitor: 2560 x 1600 @ 30Hz<br>Dual Monitor: 2048 x 1152 @ 60Hz each<br>2048 x 1152 @ 60Hz<br>2-ch Stereo (via HDMI)  |
| Software                     | OS Compatibility  | Windows 7, 8, 10<br>Mac OSX  |
| Power                        | Power Source<br>Power Adaptor Type<br>Power Consumption<br>Input Voltage<br>Power Delivery  | Bus & USB Powered<br>N/A<br>15W (Full Load)<br>5V DC @ 3A<br>N/A   |
| Physical Characteristics     | Colour<br>Shell Material<br>Host Cable Length<br>Buttons/Switches<br>LED Indicators<br>Power Cable Length<br>Product Height<br>Product Width<br>Product Length<br>Weight of Product | Black<br>ABS Plastic<br>2.1 in [53.4 mm]<br>None<br>Power: Blue<br>20.98 in [533 mm]<br>0.77 in [19.5 mm]<br>6.16 in [156.5 mm] (w SD card reader)<br>2.69 in [68.3 mm]<br>5.22 oz [148 g]   |
| Environmental                | Operating Temperature<br>Storage Temperature  | 32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condensing)<br>14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condensing)   |
| Packaging Information        | Package Type<br>Package Height<br>Package Width<br>Package Length<br>Shipping (Package) Weight  | Box<br>7.09 in [180 mm]<br>4.45 in [113.0 mm]<br>1.15 in [29.3 mm]<br>10.16 oz [288 g]   |
| What's in the Box            | Included in Package   | 1x USB 3.0 Mini Dock<br>1x MicroUSB Type-B to USB Type-A Power Cable<br>1x User Manual   |
| Notes / Special Requirements | Notes   | SD/Micro SD card reader is detachable. When in use it consumes 1 available USB 3.0 Type-A port.  |

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

