

4XEM USB 3.0 Universal Docking Station With Vertical Stand

4XEM Part- 4XUG39DK1V



Simplify your workspace with our Universal Dock with Vertical stand. This powerful device is equipped with a variety of ports to connect all your devices and peripherals, including 1x HDMI 1.2, 1x DVI-I SL, 1x USB 3.0 Type-A (5Gbps – Fast Charging), 1x USB 3.0 Type-A (5Gbps), 4x USB 2.0 Type-A (480Mbps), 1x RJ-45 (10/100/1000Mbps), and Audio Input and Output for speakers and microphone.

With this dock, you can easily connect your laptops, desktops, and other devices to one central hub. The fast charging USB 3.0 port and Gigabit Ethernet port ensure your devices stay powered and connected, while the Audio Input and Output allow you to connect external speakers and microphone.

The Universal Dock is designed to be the ultimate solution for all your connectivity needs, providing a versatile and efficient way to organize your workspace.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features

- 1x HDMI 1.2 port: Connect to external displays for high-definition video and audio.
- 1x DVI-I SL port: Connect to DVI-enabled devices for added versatility
- 1x USB 3.0 Type-A (5Gbps – Fast Charging): Quickly charge your devices and transfer data at high speeds.
- 1x USB 3.0 Type-A (5Gbps): Transfer data at high speeds.
- 4x USB 2.0 Type-A (480Mbps): Connect to peripherals such as keyboard, mouse, and more.
- 1x RJ-45 (10/100/1000Mbps): Enjoy fast and stable wired Internet connection.
- Audio Input and Output: Connect external speakers and microphone for improved audio quality.
- Universal compatibility: Windows (Vista, 7, 8, 8.1, 10), Mac OS (10.2 or higher) and Linux compatible
- Vertical stand attachment included in package

Application

- Home theatre
- Small business
- Home Office
- Business Presentations

4XEM Products Are Available At Your Favorite Online Retailers



Warranty Information	Warranty	2 Years
Features/Hardware	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Power Delivery Lock Slot Industry Standards	No 2 6 1 Yes No Yes No Yes HDMI 1.2 DVI-I SL HDCP 1.4 Battery Charging (BC 1.2) DisplayLink - DL3900 VIA - VL82B2 FE1.1S
	Chipset ID	
Connector(s)	Host Bus Type Host Connector Host Connector Cable Connector Type(s)/Rate(s)	USB 3.1 Gen 1 (5Gbps) USB Type-B (SuperSpeed) Detachable 1x HDMI 1.2 (4.95Gbps) 1x DVI-I SL (4.95Gbps) 1x USB Type-A (5Gbps - Fast Charging) 1x USB Type-A (5Gbps) 4x USB Type-A (480Mbps) 1x RJ-45 (10/100/1000Mbps) 1x 3-pole TRS 3.5mm Phono Jack - Audio In 1x 3-pole TRS 3.5mm Phono Jack - Audio Out
Performance	Maximum Digital Resolution Maximum Analog Resolution Audio Specification	Single Monitor: 2560 x 1440 @ 30Hz Dual Monitors: 2048 x 1152 @ 60Hz Each 2048 x 1152 @ 60Hz (Analog via DVI->VGA Adaptor) 2-ch Stereo
Software	OS Compatibility	Windows Vista, 7, 8, 8.1, 10 Mac OS 10.2 or higher Linux
Power	Power Source Power Adapter Style Power Consumption Input Voltage Power Delivery	Included AC Adapter (100-240VAC, 50/60Hz, 0.1A Max , CLASS II) Wall Wart 24W 12V DC @ 2A N/A
Physical Characteristics	Color Shell Material Stand Material Host Cable Length Buttons/Switches LED Indicators Power Cable Length Product Height Product Width Product Length Weight of Product Product Height (w/ Stand) Product Width (w/ Stand) Product Length (w/ Stand) Weight of Product (w/ Stand)	Black ABS Plastic Steel 2.33 ft [0.71 m] None Power: Blue 3.83 ft [1.17 m] 1.3 in [33 mm] 8.82 in [224 mm] 3.43 in [87 mm] 9.67 oz [274 g] 9.02 in [229 mm] 5.51 in [140 mm] 5.51 in [140 mm] 17.64 oz [500 g]
Environmental	Operating Temperature Storage Temperature	32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condensing) 14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Box 2.44 in [62 mm] 13.62 in [346 mm] 6.02 in [153 mm] 1.95 lbs [0.89 kg]
What's in the Box	Included in Package	1x USB Universal Docking Station 1x USB Type-B to Type-A Cable 1x DVI to VGA Adapter 1x 12V/2A Power Adapter 1x Quick Start Guide 1x Vertical Stand Assembly
Notes / Special Requirements	Notes	HDCP not supported on Mac OS or Linux

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

