



4XEM's Deluxe USB-C Travel Mini Dock with 100W PD

4XEM Part- 4XUHP3409



Introducing our USB Type C Mini Dock with 100W Power Delivery, perfect for the modern professional on-the-go. With 1x USB-C 3.1 host connector, 1x HDMI 1.4, and 3x USB ports, including a USB 3.1 Gen 1 Type-C port and a USB 3.0 Type-A port, you'll have all the connectivity you need to get your work done efficiently.

Plus, with lightning-fast data transfer speeds of up to 5Gbps and SD card readers for both standard and micro cards, you can easily access and transfer files from all your devices. And for those who need to stay connected to the internet, our mini dock includes an RJ-45 port with speeds of up to 10/100/1000Mbps.

The USB Type C Mini Dock is designed to provide maximum convenience without sacrificing performance. With its sleek and compact design, it's easy to take with you wherever you go. And with 100W Power Delivery, you can even charge your laptop while using it.

**4XEM Products Are Available At Your Favorite Online Retailers** 

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





## **DATA SHEET**

## **Features**

- USB Type C Mini Dock with 100W Power Delivery
- 1x USB-C 3.1 Host Connector
- 1x HDMI 1.4 (10.2 Gbps)
- 1x USB 3.1 Gen 1 Type-C (5Gbps Or USB-C Power Adapter for PD)
- 1x USB 3.0 Type-A (5Gbps)
- 1x USB 2.0 Type-A (480Mbps)
- 1x SD Card Reader (SD v3.01)
- 1x Micro SD Card Reader (SD v3.01)
- 1x RJ-45 (10/100/1000Mbps)



### **Benefits:**

- Versatile connectivity: The USB Type C Mini Dock features a variety of ports to connect all your devices, including a USB-C 3.1 host connector, HDMI, USB 3.1 Gen 1 Type-C, USB 3.0 Type-A, USB 2.0 Type-A, SD card reader, micro SD card reader, and RJ-45 Ethernet port.
- High-speed data transfer: With data transfer speeds of up to 5Gbps and 10.2Gbps, the Mini Dock enables fast and efficient file transfer between all connected devices.
- Power delivery: The 100W Power Delivery allows for quick and convenient charging of your laptop while using the Mini Dock.
- Compact and portable: The sleek and compact design of the Mini Dock makes it easy to carry with you wherever you go, making it ideal for professionals who are frequently on-the-go.
- Easy access to files: With both SD and micro-SD card readers, you can easily access and transfer files from all your devices.
- Reliable internet connection: The RJ-45 Ethernet port provides a reliable and fast internet connection, with speeds of up to 10/100/1000Mbps.

# **Application**

- Home theatre
- Small business
- Travel
- · Business Presentations

4XEM Products Are Available At Your Favorite Online Retailers

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





#### **DATA SHEET**

Warranty Information Warranty 2 Years

Hardware 4K Support Yes Displays Supported **USB Ports** 2 Fast-Charge Port(s) N/A Network Yes

SD Card Reader No Audio Yes\* Host Bus Type USB Type-C Power Delivery PD Pass-through No HDMI 1.4 Lock Slot Industry Standards

HDCP 1.4 HDCP 2.3

Secure Digital (SD v3.01) Power Delivery (PD 2.0) Fresco Logic FL5002 Chipset ID Parade Technologies PS176

Genesys Logic GL3510 Realtek RTL8153B

USB Type-C (5Gbps) Fixed Attached Connector(s) Host Connectors Host Connector Cable

1x HDMI 1.4 (10.2 Gbps) Connector Type(s)/Rate(s)

1x USB Type-C (5Gbps - Or USB-C Power Adapter for PD)

1x USB Type-A (5Gbps) 1x USB Type-A (480Mbps) 1x SD Card Reader (104 MB/s) 1x Micro SD Card Reader (104 MB/s) 1x RJ-45 (10/100/1000Mbps)

Maximum Digital Resolutions 4K UHD (3840 x 2160 @ 30Hz) Performance

Audio Specification 2-ch Stereo (via HDMI)

Software OS Compatibility Windows 10 Mac OSX

> **Bus Powered** Power Source Power Adaptor Style

Power Consumption 15W (full load without PD) Input Voltage PD Pass-through - Max 100W Power Delivery

Physical Characteristics Grey

Colour Shell Material Aluminum Host Cable Length 20.0 in [508 mm] Buttons/Switches Power: Blue LED Indicators Network (Link): Green

Network (Activity): Amber Power Cable Length

0.45 in [11.5 mm] 0.50 in [12.7 mm] @ network port Product Width 1.42 in [36.0 mm]

Product Length 5.24 in [133.2 mm] Weight of Product 2.72 oz [77 g]

Environmental Operating Temperature 32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condnesing) 14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condnesing) Storage Temperature

Packaging Information Package Type Package Height

Product Height

6.78 in [172.3 mm] Package Width 2.85 in [72.5 mm] 0.99 in [25.1 mm] Package Length Shipping (Package) Weight 3.88 oz [110 g] 1x USB-C Mini Dock

What's in the Box Included in Package 1x User Manual

Notes / Special Requirements Notes "DP Alt mode support required from host for HDMI output. 2 SuperSpeed data lanes used for DP Alt mode, 2 remaining SuperSpeed data

lanes used for remaining functions.

Audio out only available via HDMI.



Power

<sup>\*</sup> Product appearance and specifications are subject to change without notice.

<sup>\*</sup> Same day shipping is only available for orders shipping within the United States.