

4XEM's 15W 2xUSB-C PD Charging Kit with Interchangeable Wall Adapters

4XEM Part- 4XUNIKITATT



For your convenience 4XEM has put together this all in one charging kit. Packaged together are our 15W Double USB-C wall adapter with 6 different wall plug in adapters for various countries and two USB cables. Both cables are capable of 480Mbps data rate for fast charging and transferring with the USB-C to USB-C cable. The adapter is capable of 15W power delivery (PD) charging with both ports being able to work simultaneously. Tested for over heating and burn all three products will work safely and in conjunction with another to keep you fully charged wherever you may need.



## Features

- Compatibility with Samsung, Apple and any USB-C and Micro USB device
- 1x USB-C to Micro USB Cable
- 1x USB-C to USB-C (Not E-Marked)
- 15Watt power PD fast charging Wall Adapter
- 6x Interchangeable wall outlet plugs for various Countries (India, Australia, China, Argentina, EU-South Africa and UK)
- 2x USB-C port on Wall Charger
- 480Mbps Data Rate
- Meets USB-PD 3.0 and USB 2.0 Industry Standards



## Application

- Charging
- At Home
- At the Office
- Travel



## Universal Adapter Specs

Warranty Information	Warranty	1 year
Connector(s)	Charging Port (s) Power	2x USB Type-C Non-Polarized NEMA 1-15P (Canada, Japan, USA) Fixed with Retractable Prongs Pack of global AC input form adapters included
Performance	Industry Standards	USB-PD 3.0 USB 2.0
Physical Characteristics	Charger Colour Display LED Indicator(s) Charger Width Charger Height Charger Length  Charger Weight	Black No None 1.149 in [29.2 mm] 1.59 in [40.56 mm] 1.71 in [43.6 mm] 2.34 in [59.6 mm] (with power prongs out ) 1.83 oz [52 g]
Power	Total Power Budget Power Delivery Input Voltage Output Voltage (Port 1/2)  Output Voltage (Ports 1&2)	15W 15W 100-240 VAC, 50Hz-60Hz @ 0.8A 5V DC @ 2.4A 9V DC @ 1.67A 12V DC @ 1.25A 5V DC @ 3A (Shared)
Environmental	Operating Temperature Storage Temperature Humidity	32°F to 104°F [0°C to 40°C] -4°F to 176°F [-20°C to 80°C] 5% to 90% (non-condensing)
Packaging Information	Package Type Package Width Package Height Package Length Shipping (Package) Weight	Box 4.42 in [112.2 mm] 3.73 in [94.7 mm] 2.85 in [72.5 mm] 7.34 oz [208 g]
What's in the Box	Included in Package	1x 15W Dual USB-C Charger 1x Pack of global AC input form adapters
Notes	Notes	"Included global AC form adapters are: GB 1002-2008 (China) EN 50075 (EU-South Africa) IS 1293 (India) BS 1363-1 (UK) AS/NZS 3112 (Australia) IRAM 2063 (Argentina) Measurements of charger taken without any of the included global AC input adapters."

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.



## USB-C to Micro USB-B Cable Specs

Warranty Information	Warranty	1 Year
Hardware	Operating Mode Direction Industry Standards E-Marked	Passive Bidirectional USB 2.0 N/A
Connector(s)	Connector A Connector B	USB Type-C - Male Micro USB Type-B - Male
Performance	Data Transfer Rate	Hi-Speed USB - 480 Mbps
Physical Characteristics	Colour Connector Plating Connector Style Cable Jacket Type Wire Gauge Cable OD Cable Length Weight of Product	White Nickel Straight PVC 2C @ 22 AWG + 3C @ 28 AWG 0.15 in [3.8 mm] 3.28 ft [1.00 m] 1.06 oz [30 g]
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Poly-bag 6.00 in [152.4 mm] 4.00 in [101.6 mm] 0.48 in [12.3 mm] 1.20 oz [34 g]

\* Product appearance and specifications are subject to change without notice.  
Weights are approximate.  
Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep**  
**1-866-999-4936 Ext.104    tschaus@4xem.com**



## USB-C to USB-C Charging Cable Specs

Warranty Information	Warranty	1 Year
Hardware	Operating Mode	Passive
	Direction	Bidirectional
	Industry Standards	USB 2.0
	E-Marked	No
Connector(s)	Connector A	USB Type-C - Male
	Connector B	USB Type-C - Male
Performance	Data Transfer Rate	Hi-Speed USB - 480 Mbps
Physical Characteristics	Colour	Black
	Connector Plating	Nickel
	Connector Style	Straight
	Cable Jacket Type	PVC
	Wire Gauge	2C @ 22 AWG + 3C @ 28 AWG
	Cable OD	0.15 in [3.8 mm]
	Cable Length	3.28 ft [1.00 m]
	Weight of Product	1.06 oz [30 g]
Packaging Information	Package Type	Poly-bag
	Package Height	6.00 in [152.4 mm]
	Package Width	4.00 in [101.6 mm]
	Package Length	0.48 in [12.3 mm]
	Shipping (Package) Weight	1.20 oz [34 g]

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep**  
**1-866-999-4936 Ext.104    tschaus@4xem.com**

