



4XEM Universal USB Power Adapter/Wall Charger for all USB devices 4port

4XEM PART - 4XUSBCHARGER4



4XEM's compact 2.1 AMP 4Port USB Wall Charger will charge your iPad (including Retina display iPads) and other iDevices without the need for a separate computer. Quickly plugs into a standard household outlet for fast, efficient charging. Connect the adapter directly to your iDevice via a separate 8-Pin Lightning or 30-Pin to USB Cable connector. Also charges all iPhone/iPod models and compatible MP3 players, digital cameras, tablets, mobile phones and other devices.

Problem it solves: No need to connect your iDevice to a computer for recharging. With the Power Adapter/Wall Charger, you can easily plug into any household outlet for a quick boost! Charge up to 4different devices simultaneously!

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

Features:

- •4XEM unmatched lifetime warranty
- For all USB mobile phones and tablets
- For iPhones 5/5c/5s/SE/6/6 Plus/6s/6s Plus/7 7 Plus
- For iPads with Retina/ mini/mini 2/ Air/2/3/4 and Pros
- For iPods nano 7th Generation/touch 5th Gen./6th Gen.
- Output Voltage: 5V
- Maximum Output Power: 5W
- Charge up to 4 devices

Application(s):

- Power Delivery
- Portable Charging
- Travel
- Home/Office use
- Mobile Power
- USB devices





4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

| Warranty Information | Warranty | 1 year |
|--------------------------|---|---|
| Connector(s) | Charging Port(s) Power Source | 4x USB Type-A Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Removable with Retractable Prongs (Reveals Non-Polarized IEC 320 C7/C8 Connection when removed) |
| Performance | Industry Standards | N/A |
| Physical Characteristics | Colour Display LED Inidicator Power Cable Length Product Height Product Width Product Length Weight of Product | White No Power: Red N/A 2.45 in [62.2 mm] 1.41 in [29.0 mm] 2.29 in [58.2 mm] 2.93 in [74.5 mm] (with power prongs out) 2.40 oz [68 g] |
| Power | Total Power Budget Power Delivery Input Voltage Output Voltage | 20W N/A 110-240VAC, 50Hz-60Hz @ 0.5A 5V DC @ 2.1A |
| Environmental | Operating Temperature Storage Temperature Humidity | 0°C to 40°C (32°F to 104°F) -20°C to 80°C (-4°F to 176°F) 5% to 90% (non-condensing) |
| Packaging Information | Package Type Package Height Package Width Package Length Shipping (Package) Weight | Poly-Bag 5.91 in [150 mm] 3.94 in [100 mm] 1.17 in [29.7 mm] 2.47 oz [70 g] |
| What's in the Box | Included in Package | 1x 4-port USB Charger |
| Notes | Notes | Maximum power output per port is 10W. Total power output cannot exceed 20W. |

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com